




Lenovo 01CV830 network card Internal Fiber 16000 Mbit/s

Brand : Lenovo

Product code: 01CV830

Product name : 01CV830




Emulex 16Gbps Gen 6 FC Single-Port HBA Adapter for Lenovo System X Servers

[Lenovo 01CV830 network card Internal Fiber 16000 Mbit/s:](#)

The Emulex 16 Gb (Generation 6) Fibre Channel (FC) host bus adapters (HBAs) are an ideal solution for all Lenovo System x servers requiring high-speed data transfer in storage connectivity for virtualized environments, data backup, and mission-critical applications. They are designed to meet the needs of modern networked storage systems that utilize high performance and low latency solid state storage drives for caching and persistent storage as well as hard disk drive arrays.

The Emulex 16 Gb Gen 6 FC HBAs feature ExpressLane™, which prioritizes mission-critical traffic in congested networks ensuring maximum application performance on flash storage arrays. They also seamlessly support Brocade ClearLink™ diagnostics through Emulex OneCommand® Manager, ensuring the reliability and management of storage network when connected to Brocade Gen 5 FC SAN fabrics.

Ports & interfaces		Design	
Connectivity technology *	Wired	Compatible products	System x3500 M5 Type 5464
Host interface *	PCIe		System x3550 M5 Type 5463
Interface *	Fiber		System x3550 M5 Type 8869
Fiber ports quantity	1		System x3650 M5 Type 5462
Fiber optic connector	FC, SFP+		System x3650 M5 Type 8871
PCI version	3.0		System x3750 M4 Type 8753
Network			System x3850 X6 Type 6241 (E7 v2, E7 v3, and E7 v4) System x3950 X6 Type 6241 (E7 v2, E7 v3, and E7 v4) NeXtScale nx360 M5 Type 5465 (E5-2600 v3 and E5-2600 v4)
Maximum data transfer rate *	16000 Mbit/s	System requirements	
Full duplex	✓	Linux operating systems supported	RedHat EL Linux 6.0, RedHat EL Linux 7.0, SuSE Linux 11, SuSE Linux 12.0
Web-based management	✓	Other operating systems supported	VMware vSphere ESXi
Maximum operating distance	150 m	Server operating systems supported	Windows Server 2012, Windows Server 2012 R2
Design		Operational conditions	
Component for *	Server	Operating temperature (T-T)	0 - 55 °C
Product colour	Black, Green, Silver	Storage temperature (T-T)	-20 - 85 °C
Internal *	✓	Operating relative humidity (H-H)	5 - 95%
Rack mounting	✓	Sustainability	
Rack capacity	2U	Sustainability certificates	RoHS
Hot-swap	✓	Weight & dimensions	
Hot-Plug support	✓	Depth	168 mm
LED indicators	✓	Height	69 mm
Mean time between failures (MTBF)	10000000 h	Packaging data	
	AS/NZS CISPR22:2009+A1, Class A Australian EMC Framework (RCM) cUR recognized to CSA 22.2, No. 60950-1-07 EN55022:2010, Class A EN55024:2010 EN55032:2012 EU (CE Mark) FCC Rules, Part 15, Class A Industry Canada, ICES-003, Class A Japan VCCI, Class A Korea MSIP, Class A RoHS Compliant (Directive 2011/65/EU) TUV certified to EN60950-1+A11+A1+A12+A2 Taiwan BSMI, Class A UL recognized to UL60950-1 2nd Edition	Quantity	1
Certification		Low-profile bracket	✓
		Package type	Box
		Packaging content	
		Mounting brackets included	✓
		Logistics data	
		Harmonized System (HS) code	85176990
		Other features	
		PCI-SIG* SR-IOV Capable	✓



0889488417339



889488417339

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.