

Market segment

Server

## Lenovo Intel Xeon E5-2430 v2 processor 2.5 GHz 15 MB L3

Brand: Lenovo Product code: 0C19564

**Product name :** Intel Xeon E5-2430 v2

Intel Xeon E5-2430 v2, 2.5 GHz (3 GHz Turbo), 15 MB Cache, 7.2 GT/s, 22 nm

Lenovo Intel Xeon E5-2430 v2 processor 2.5 GHz 15 MB L3:

Lenovo has been the fastest growing major PC company for more than 4 years, but we're much more than a PC company. We create a full range of personal technology, including smartphones, tablets and smart TVs. We're the fourth largest smartphone company in the world, and are expanding rapidly to new markets. And we're already #3 in the world in what IDC calls "Smart Connected Devices," which combines PCs, smartphones and tablets.

Lenovo Intel Xeon E5-2430 v2. Processor family: Intel® Xeon® E5 V2 Family, Processor socket: LGA 1356 (Socket B2), Processor lithography: 22 nm. Memory channels: Triple-channel, Maximum internal memory supported by processor: 384 GB, Memory types supported by processor: DDR3-SDRAM. Market segment: Server, Scalability: 2S. Package width: 42.5 mm, Package depth: 45 mm. Intel® Virtualization Technology (Intel® VT): VT-d, VT-x





Processor		Features	
Processor model *	E5-2430V2	PCI Express slots version	3.0
Processor base frequency *	2.5 GHz	Scalability	2S
Processor family *	Intel® Xeon® E5 V2 Family	Embedded options available	1
Processor cores * 6		Processor special features	
Processor socket *	LGA 1356 (Socket B2)	Intel® Hyper Threading Technology	
Component for	Server/workstation	(Intel® HT Technology)	✓
Processor lithography *	22 nm	Intel® Identity Protection	×
Processor threads	12	Technology (Intel® IPT)	
System bus rate	7.2 GT/s	Intel® Turbo Boost Technology	2.0
Processor operating modes *	32-bit, 64-bit	Intel Flex Memory Access	×
Processor boost frequency	3 GHz	Intel® Smart Cache	✓
Processor cache Processor cache type	15 MB L3	Intel® AES New Instructions (Intel® AES-NI)	✓
Thermal Design Power (TDP)	80 W	Enhanced Intel SpeedStep Technology	✓
/ID Voltage Range	0.65 - 1.30 V	Intel Trusted Execution Technology	1
Bus type Number of QPI links	QPI 1	Intel VT-x with Extended Page Tables (EPT)	✓
Memory bandwidth supported by	38.4 GB/s	Intel Demand Based Switching	1
processor (max)	30.4 (3)/3	Intel® Secure Key	1
<b>demory</b>		Intel TSX-NI	×
Maximum internal memory supported by processor	384 GB	Intel Virtualization Technology (VT-x)	✓
Memory types supported by processor	DDR3-SDRAM	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Memory clock speeds supported by	800,1066,1333,1600 MHz	Intel® vPro™ Platform Eligibility	✓
orocessor Memory channels *	Triple-channel	Operational conditions	
ECC	√	Tcase	76 °C
Graphics		Packaging data	
On-board graphics card *	×	Package width	42.5 mm
<u> </u>		Package depth	45 mm
eatures		Other features	
Execute Disable Bit Idle States	<b>*</b>	Intel® Virtualization Technology (Intel® VT)	VT-d, VT-x
Thermal Monitoring Technologies			
	•		

