

Lexmark X264dn Laser A4 1200 x 1200 DPI 28 ppm

Brand : Lexmark

Product code: 13B0500

Product name : X264dn

X264dn, Monochrome Laser, 28ppm, 1200 x 1200dpi, Duplex, Network, 19.5kg

[Lexmark X264dn Laser A4 1200 x 1200 DPI 28 ppm:](#)

Compact, reliable and ideal for small workgroups, the Lexmark X264dn MFP delivers rapid printing, copying, scanning and faxing - with output speeds up to 28 ppm. Zip through workloads quickly and easily with the 50-sheet automatic document feeder. And reduce paper waste by printing in duplex or scanning straight to email.

- Compact and reliable MFP for small workgroups
- Print, copy, scan and fax
- Up to 28 ppm print speed
- First page out as fast as 7.5 seconds
- 64MB of RAM standard
- Up to 250-sheet input and single-sheet priority bypass feed
- Ships with 1,500-page Lexmark Return Program Toner Cartridge
- Choice of replacement toner cartridge yields: 3,500 or 9,000 pages
- Recommended monthly volume: 250 to 4,500 pages



Printing		Ports & interfaces	
Print technology *	Laser	Direct printing *	✗
Printing *	Mono printing	USB port	✓
Duplex printing *	✓	USB 2.0 ports quantity	1
Maximum resolution *	1200 x 1200 DPI	Network	
Print speed (black, normal quality, A4/US Letter) *	28 ppm	Wi-Fi *	✗
Duplex print speed (black, normal quality, A4/US Letter)	15 ppm	Ethernet LAN *	✓
Time to first page (black, normal)	7.5 s	Supported network protocols (IPv4)	✓
Print margins (top, bottom, right, left)	4 mm	Supported network protocols (IPv6)	✓
Economical printing	✓	Network printing methods	LPR/LPD Direct IP (Port 9100) HTTP Enhanced IP (Port 9400) FTP, TFTP IPP 1.1
Print speed (colour, fast normal, letter)	30 ppm	Performance	
Copying		Maximum internal memory	64 MB
Copying *	Mono copying	Card reader integrated	✗
Copy speed (black, normal quality, A4)	28 cpm	Internal memory *	64 MB
Time to first copy (black, normal)	8.5 s	Processor frequency	266 MHz
Copier resize	25 - 400%	Sound pressure level (printing)	54 dB
Scanning		Sound pressure level (duplex printing)	52 dB
Scanning *	Colour scanning	Sound pressure level (copying)	54 dB
Optical scanning resolution *	600 x 600 DPI	Sound pressure level (scanning)	51 dB
Maximum scan area	Legal (216 x 356)	Sound power level (standby)	27 dB
Scanner type *	Flatbed & ADF scanner	Mac compatibility	✓
Scan to	E-mail, File	Design	
Scan speed (black)	21 ppm	Market positioning *	Business
Fax		System requirements	
Faxing *	Mono faxing	Windows operating systems supported	Windows 2000
Modem speed	33.6 Kbit/s	Mac operating systems supported	Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion
Features		Linux operating systems supported	✓
Maximum duty cycle *	50000 pages per month	Server operating systems supported	Windows 2000 Server, Windows Server 2003, Windows Server 2008
Digital sender	✗		
Number of print cartridges *	1		
Printing colours *	Black		

Features		System requirements	
Page description languages	PCL 5e, PCL 6, PostScript 3, PPDS	Other operating systems supported	Novell NetWare 5.x, Novell NetWare 6.x, Novell Open Enterprise Server
Input & output capacity		Operational conditions	
Total number of input trays *	2	Operating relative humidity (H-H)	8 - 80%
Total input capacity *	250 sheets	Operating temperature (T-T)	16 - 32 °C
Total output capacity *	150 sheets	Operating altitude	0 - 2500 m
Multi-Purpose tray	✓	Certificates	
Multi-Purpose tray input capacity	1 sheets	Certification	Blue Angel (RAL-UZ-122), U.S. FDA, FCC B, UL 60950-1, IEC 60320-1, ECMA 74:8, CAN/CSA-C22.2 60950-1-03, ICES-003 B, VCCI B, BSMI B, CE B, CB IEC 60950-1, IEC 60825-1, IEC 61000-3-2, IEC 61000-3-3, EN 55022 B, EN 55024, CISPR 22 B, IEC 60320, GS (TÜV), EN 60825-1, ACMA A-tick mark B, AS/NZS 60950-1, EK Mark, K60950, KCC MIC Mark, CCC B, UL AR, CS, TÜV Rh, PSB-SS 337, CNS 13438, CNS 14336
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	50 sheets		
Auto document feeder (ADF) output capacity	50 sheets		
Maximum number of input trays	3		
Maximum input capacity	800 sheets		
Maximum output capacity	150 sheets		
Paper handling		Sustainability	
Maximum ISO A-series paper size *	A4	Sustainability certificates	ENERGY STAR
Maximum print size	216 x 356 mm	Weight & dimensions	
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Weight	19.5 kg
ISO A-series sizes (A0...A9) *	A4, A5	Packaging content	
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement	Drivers included	✓
JIS B-series sizes (B0...B9)	B5	Other features	
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Dimensions (WxDxH)	428 x 405 x 440 mm
Ports & interfaces		Network ready	✓
Standard interfaces	Ethernet, USB 2.0	A6 Card	✓
		Finishing option	✗
		All-in-one functions	Copy, Fax, Print, Scan
		Colour all-in-one functions	Scan
		Package dimensions (WxDxH)	508 x 473 x 570 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date