

Lexmark MX710de Laser A4 1200 x 1200 DPI 60 ppm

Brand : Lexmark

Product code: 24T7401

Product name : MX710de

Laser, 1200 x 1200 dpi, 60 ppm/60 cpm, 7" e-Task Touch, Gigabit Ethernet, USB 2.0, 43.3 kg
 Lexmark MX710de. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 1200 x 1200 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, Grey



Printing		Ports & interfaces	
Print resolution black	1200 x 1200 DPI	USB 2.0 ports quantity	3
Print technology *	Laser	Optional connectivity	Parallel, Serial (RS-232), Wireless LAN
Printing *	Mono printing		
Duplex printing *	✓		
Maximum resolution *	1200 x 1200 DPI		
Print speed (black, normal quality, A4/US Letter) *	60 ppm		
Duplex print speed (black, normal quality, A4/US Letter)	36 ppm		
Time to first page (black, normal)	4.4 s		
Copying		Network	
Duplex copying *	✓	Wi-Fi *	✗
Copying *	Mono copying	Ethernet LAN *	✓
Maximum copy resolution *	1200 x 1200 DPI	Security algorithms	802.1x RADIUS, LEAP, MD5, PEAP
Copy speed (black, normal quality, A4)	60 cpm	Supported network protocols (IPv4)	TCP/IP, AppleTalk
Time to first copy (black, normal)	4.2 s	Supported network protocols (IPv6)	TCP/IP, TCP, UDP
Copier resize	25 - 400%	Management protocols	HTTP, HTTPS (SSL*/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger
		Network printing methods	LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400) FTP, TFTP, IPP 1.0, 1.1, 2.0
Scanning		Performance	
Duplex scanning *	✓	Maximum internal memory	2560 MB
Scanning *	Colour scanning	Internal memory *	512 MB
Optical scanning resolution *	600 x 600 DPI	Processor frequency	800 MHz
Maximum scan area	216 x 356 mm	Sound pressure level (printing)	57 dB
Scanner type *	Flatbed & ADF scanner	Sound pressure level (duplex printing)	57 dB
Scan technology	CCD	Sound pressure level (copying)	58 dB
Scan speed (colour)	70 ppm	Sound pressure level (scanning)	57 dB
Scan speed (black)	70 ppm	Sound power level (standby)	33 dB
Duplex scan speed (colour)	68 ppm	Mac compatibility	✓
Duplex scan speed (black)	72 ppm		
Fax		Design	
Duplex faxing	✓	Product colour *	Black, Grey
Faxing *	Mono faxing	Market positioning *	Business
Modem speed	33.6 Kbit/s	Display diagonal	17.8 cm (7")
		Touchscreen	✓
		Control type	Touch
Features		System requirements	
Maximum duty cycle *	275000 pages per month	Mac operating systems supported	Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion
Digital sender	✗		
Page description languages	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PostScript 3, PPDS		
Country of origin	China		

Input & output capacity		System requirements	
Total number of input trays *	2		Fedora 14, Fedora 15, RedHat EL Linux 4.0 U5, RedHat EL Linux 4.0 U6, RedHat EL Linux 4.0 U7, RedHat EL Linux 5.0, RedHat EL Linux 5.1, RedHat EL Linux 5.2, RedHat EL Linux 5.3, SuSE Linux 10, SuSE Linux 10.2, SuSE Linux 10.3, SuSE Linux 11
Total input capacity *	650 sheets		
Total output capacity *	550 sheets		
Auto document feeder (ADF)	✓	Linux operating systems supported	
Auto document feeder (ADF) input capacity	150 sheets		
Auto document feeder (ADF) output capacity	150 sheets	Server operating systems supported	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64
Maximum number of input trays	5		
Maximum input capacity	3300 sheets	Other operating systems supported	Novell NetWare 5.x, Novell NetWare 6.x, Novell Open Enterprise Server
Maximum output capacity	550 sheets		
Paper handling		Operational conditions	
Maximum ISO A-series paper size *	A4	Operating relative humidity (H-H)	8 - 80%
Maximum print size	216 x 356 mm	Operating temperature (T-T)	16 - 32 °C
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Operating temperature (T-T)	60 - 90 °F
ISO A-series sizes (A0...A9) *	A4, A5, A6	Operating altitude	0 - 2896 m
ISO B-series sizes (B0...B9)	B5	Sustainability	
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement	Sustainability certificates	ENERGY STAR
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Weight & dimensions	
Ports & interfaces		Width	548 mm
Standard interfaces	Ethernet, USB 2.0	Depth	578 mm
Direct printing *	✓	Height	727 mm
USB port	✓	Weight	43.3 kg
		Packaging data	
		Package width	735 mm
		Package depth	700 mm
		Package height	1017 mm
		Package weight	57.1 kg
		Other features	
		Finishing option	✗
		Package dimensions (W x D x H)	735.1 x 700 x 1017 mm (28.9 x 27.6 x 40")
		Supported media weight(s)	60 - 176 g/m ²
		All-in-one functions	Copy, Fax, Print, Scan
		Colour all-in-one functions	Scan



0734646355476



734646355476

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.