

Lexmark MX722adhe Laser A4 1200 x 1200 DPI 66 ppm

Brand : Lexmark

Product code: 25B0001

Product name : MX722adhe

Lexmark MX722adhe. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying. Scanning: Colour scanning. Faxing: Mono faxing. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, White



Printing		Ports & interfaces	
Print technology *	Laser	USB port	✓
Printing *	Mono printing	USB connector	USB Type-A / USB Type-B
Duplex printing *	✓	USB 2.0 ports quantity	3
Maximum resolution *	1200 x 1200 DPI	Optional connectivity	Parallel, Serial (RS-232), Wireless LAN
Print speed (black, normal quality, A4/US Letter) *	66 ppm	Network	
Time to first page (black, normal)	4 s	Wi-Fi *	✗
Copying		Ethernet LAN *	✓
Duplex copying *	✓	Cabling technology	10/100/1000Base-T(X)
Copying *	Mono copying	Ethernet LAN data rates	10,100,1000 Mbit/s
Copy speed (black, normal quality, A4)	66 cpm	Security algorithms	802.1x RADIUS, IPSEC, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, TTLS
Time to first copy (black, normal)	4 s	Management protocols	DHCP, APIPA (AutoIP), BOOTP, RARP, mDNS, IGMP, Bonjour, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL/TLS), Finger
Copier resize	25 - 400%	Mobile printing technologies	Apple AirPrint
Scanning		Performance	
Duplex scanning *	✓	Maximum internal memory	6144 MB
Scanning *	Colour scanning	Internal memory *	2048 MB
Maximum scan area	215.9 x 355.6 mm	Built-in processor	✓
Scanner type *	Flatbed & ADF scanner	Processor frequency	1200 MHz
Scan technology	CCD	Processor cores	4
Scan to	E-mail, FTP, USB	Sound pressure level (printing)	57 dB
Image formats supported	JPEG, JPG, TIFF	Sound pressure level (duplex printing)	57 dB
Document formats supported	PDF, XPS	Sound pressure level (copying)	60 dB
Fax		Sound pressure level (scanning)	56 dB
Faxing *	Mono faxing	Design	
Fax transmission speed	3 sec/page	Product colour *	Black, White
Modem speed	33.6 Kbit/s	Market positioning *	Business
Features		Built-in display *	✓
Recommended duty cycle	5000 - 100000 pages per month	Display diagonal	17.8 cm (7")
Maximum duty cycle *	350000 pages per month	Touchscreen	✓
Page description languages	PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3, XPS	Control type	Touch
Input & output capacity		Colour display	✓
Total number of input trays *	2	Power	
Total input capacity *	650 sheets	Power consumption (printing)	850 W
Total output capacity *	550 sheets	Power consumption (copying)	890 W
Multi-Purpose tray	✓	Power consumption (scanning)	73 W
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	✓		

Input & output capacity		Power	
Auto document feeder (ADF) input capacity	200 sheets	Power consumption (ready)	42 W
Auto document feeder (ADF) output capacity	200 sheets	Power consumption (sleep)	2 W
Maximum number of input trays	5	Energy Star Typical Electricity Consumption (TEC)	3.3 kWh/week
Maximum input capacity	3300 sheets	System requirements	
Maximum output capacity	550 sheets	Windows operating systems supported	✓
Paper handling		Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Maximum ISO A-series paper size *	A4	Linux operating systems supported	✓
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Operational conditions	
ISO A-series sizes (A0...A9) *	A4, A5, A6	Operating relative humidity (H-H)	8 - 80%
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Operating temperature (T-T)	10 - 32 °C
JIS B-series sizes (B0...B9)	B5	Operating altitude	0 - 2896 m
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Sustainability	
Paper tray media weight	60 - 176 g/m ²	Sustainability certificates	Blue Angel, ENERGY STAR
Ports & interfaces		Weight & dimensions	
Standard interfaces	Ethernet, USB 2.0	Width	558.8 mm
Direct printing *	✓	Depth	578.4 mm
		Height	739.1 mm
		Weight	44.1 kg



0734646612463



734646612463

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.