

Lexmark MS911de Colour 1200 x 1200 DPI A3

Brand : Lexmark

Product code: 26Z0000

Product name : MS911de

Print, A3, Mono, Duplex, 55 ppm (A4), Gigabit Ethernet, USB 2.0, e-Task 10.9cm Touchscreen

[Lexmark MS911de Colour 1200 x 1200 DPI A3:](#)

Large Format by Lexmark

High-volume output, long-life replaceable components, solid security, advanced finishing and SRA3 capability make the MS911de the ultimate large-format monochrome printer from Lexmark. Lexmark MS911de. Print technology: Laser, Colour. Maximum duty cycle: 300000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A3. Print speed (black, normal quality, A4/US Letter): 55 ppm, Duplex printing. Network ready. Product colour: Black, White



Printing		Network	
Duplex printing mode	Auto/Manual	Supported network protocols (IPv6)	TCP/IP IPv6, TCP, UDP
Print speed (colour, normal quality, A4/US Letter)	55 ppm	Management protocols	HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger
Colour *	✓	Web-based management	✓
Print technology *	Laser	Mobile printing technologies	Apple AirPrint
Duplex printing *	✓	Performance	
Maximum resolution *	1200 x 1200 DPI	Internal memory *	512 MB
Print speed (black, normal quality, A4/US Letter) *	55 ppm	Maximum internal memory	2560 MB
Time to first page (black, normal)	5.5 s	Built-in processor	✓
Features		Processor model	2-Core
Maximum duty cycle *	300000 pages per month	Processor frequency	800 MHz
Recommended duty cycle	15000 - 59000 pages per month	Sound pressure level (printing)	54 dB
Page description languages *	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PostScript 3, PPDS	Sound pressure level (duplex printing)	55 dB
Input & output capacity		Noise level (idle)	28 dB
Total number of input trays *	3	Design	
Total input capacity *	1150 sheets	Product colour *	Black, White
Total output capacity *	250 sheets	Built-in display *	✓
Paper input type	Paper tray	Display diagonal	10.9 cm (4.3")
Multi-Purpose tray	✓	Touchscreen	✓
Multi-Purpose tray input capacity	150 sheets	Control type	Touch
Maximum number of input trays	6	ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, cTUV, US FDA/CDRH, cTUVus, IEC 60825-1, CB Report, NCC Mark, FCC, CE (EU) DoC, EFTA (CE), KCC, RCM, CCC, C-tick DoC, EuP, CECP, CEL, ECMA-370, TED, GOST-R, SII, TER, Bel GISS, SABS, TUV-AR, KC mark, BIS, TUV-GS Mark	
Maximum input capacity	6650 sheets	Operational conditions	
Maximum output capacity	3500 sheets	Operating temperature (T-T)	10 - 30 °C
Paper handling		Operating relative humidity (H-H)	15 - 85%
Maximum ISO A-series paper size *	A3	Operating altitude	0 - 2500 m
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Sustainability	
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6	Sustainability certificates	ENERGY STAR
Non-ISO print media sizes	Executive, Folio, Ledger (media size), Letter, Oficio, Statement, Universal, Legal	Weight & dimensions	
JIS B-series sizes (B0...B9)	B4, B5	Width	615 mm
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Depth	697 mm
Paper tray media weight	60 - 256 g/m ²		
Ports & interfaces			
Standard interfaces	Ethernet, USB 2.0		
Direct printing *	✓		
USB 2.0 ports quantity	4		

Ports & interfaces		Weight & dimensions	
Optional connectivity	Parallel, Serial (RS-232), Wireless LAN	Height	770 mm
		Weight	74 kg
Network		Packaging data	
Network ready	✓	Package width	762 mm
Ethernet LAN *	✓	Package depth	838 mm
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Package height	965 mm
Security algorithms	802.1x RADIUS, HTTPS, LEAP, MD5, PEAP, SSL/TLS	Package weight	90 kg
Supported network protocols (IPv4)	TCP/IP IPv4, AppleTalk	Other features	
		Power LED	✓
		PictBridge	✗



0734646512558



734646512558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.