

Lexmark CX410e Laser A4 1200 x 1200 DPI 30 ppm

Brand : Lexmark

Product code: 28D0500

Product name : CX410e

Laser, 1200 x 1200 dpi, 30 ppm/30 cpm, 4.3" e-Task Touch, Gigabit Ethernet, USB 2.0, 27.39 kg
 Lexmark CX410e. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200
 DPI, Print speed (colour, normal quality, A4/US Letter): 30 ppm. Copying: Colour copying, Maximum copy
 resolution: 1200 x 1200 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 1200 DPI.
 Faxing: Colour faxing. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, Grey



Printing		Paper handling	
Print resolution colour	1200 x 1200 DPI	Paper tray media types *	Card stock, Labels, Plain paper, Transparencies
Print technology *	Laser	ISO A-series sizes (A0...A9) *	A4, A5
Printing *	Colour printing	Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio
Maximum resolution *	1200 x 1200 DPI	JIS B-series sizes (B0...B9)	B5
Print speed (black, normal quality, A4/US Letter) *	30 ppm	Paper tray media weight	60 - 176 g/m ²
Print speed (colour, normal quality, A4/US Letter)	30 ppm	Ports & interfaces	
Time to first page (black, normal)	10.5 s	Standard interfaces	Ethernet, USB 2.0
Time to first page (colour, normal)	11.5 s	Direct printing *	✓
Copying		USB port	✓
Copying *	Colour copying	USB 2.0 ports quantity	2
Maximum copy resolution *	1200 x 1200 DPI	Optional connectivity	Wireless LAN
Copy speed (black, normal quality, A4)	30 cpm	Network	
Copy speed (colour, normal quality, A4)	30 cpm	Wi-Fi *	✗
Time to first copy (black, normal)	10.8 s	Ethernet LAN *	✓
Time to first copy (colour, normal)	11.6 s	Security algorithms	802.1x RADIUS, EAP-TLS, EAP-TTLS, LEAP, MD5, PEAP
Copier resize	25 - 400%	Supported network protocols (IPv4)	TCP/IP, AppleTalk
N-in-1 copy function (N=)	4	Supported network protocols (IPv6)	TCP/IP, TCP, UDP
Scanning		Management protocols	HTTP, HTTPS (SSL*/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger
Duplex scanning *	✓	Network printing methods	LPR/LPD, Direct IP (9100), Enhanced IP (9400), FTP, TFTP, ThinPrint, Telnet, IPP 1.0, 1.1, 2.0
Scanning *	Colour scanning	Performance	
Optical scanning resolution *	600 x 1200 DPI	Maximum internal memory	2560 MB
Maximum scan area	216 x 356 mm	Card reader integrated	✗
Scanner type *	Flatbed & ADF scanner	Internal memory *	512 MB
Scan technology	CCD	Processor frequency	800 MHz
Scan speed (colour)	32 ppm	Sound pressure level (printing)	49 dB
Scan speed (black)	32 ppm	Sound pressure level (copying)	50 dB
Duplex scan speed (colour)	14 ppm	Sound pressure level (scanning)	50 dB
Duplex scan speed (black)	14 ppm	Sound power level (standby)	16 dB
Fax			
Duplex faxing	✓		
Faxing *	Colour faxing		
Fax transmission speed	3 sec/page		
Modem speed	33.6 Kbit/s		

Features		Design	
Recommended duty cycle	800 - 6000 pages per month	Product colour *	Black, Grey
Maximum duty cycle *	75000 pages per month	Market positioning *	Business
Digital sender	✗	Display diagonal	10.9 cm (4.3")
Number of print cartridges *	5	Touchscreen	✓
Printing colours *	Black, Cyan, Magenta, Yellow	Control type	Touch
Page description languages	Microsoft XPS, PCL 5c, PCL 6, PDF 1.7, PostScript 3, PPDS	System requirements	
Input & output capacity		Mac operating systems supported	Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion
Total number of input trays *	1	Linux operating systems supported	Fedora 14, Fedora 15, RedHat EL Linux 4.0 U5, RedHat EL Linux 4.0 U6, RedHat EL Linux 4.0 U7, RedHat EL Linux 5.0, RedHat EL Linux 5.1, RedHat EL Linux 5.2, RedHat EL Linux 5.3, SuSE Linux 10, SuSE Linux 10.2, SuSE Linux 10.3, SuSE Linux 11
Total input capacity *	251 sheets	Server operating systems supported	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64
Total output capacity *	150 sheets	Other operating systems supported	Novell NetWare 5.x, Novell NetWare 6.x, Novell Open Enterprise Server
Auto document feeder (ADF)	✓	Operational conditions	
Auto document feeder (ADF) input capacity	50 sheets	Operating relative humidity (H-H)	8 - 80%
Auto document feeder (ADF) output capacity	50 sheets	Operating temperature (T-T)	16 - 32 °C
Maximum number of input trays	4	Operating altitude	0 - 2896 m
Maximum input capacity	1451 sheets	Weight & dimensions	
Maximum output capacity	150 sheets	Width	444 mm
Paper handling		Depth	558 mm
Maximum ISO A-series paper size *	A4	Height	470 mm
Maximum print size	216 x 356 mm	Weight	27.4 kg
		Packaging data	
		Package width	558 mm
		Package depth	594 mm
		Package height	567 mm
		Package weight	31.4 kg
		Other features	
		All-in-one functions	Copy, Fax, Print, Scan
		Colour all-in-one functions	Copy, Fax, Print, Scan

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date