

Lexmark CX410de Laser A4 1200 x 1200 DPI 30 ppm

Brand : Lexmark

Product code: 28D0550

Product name : CX410de

Laser, 1200 x 1200 dpi, 30 ppm/30 cpm, 4.3" e-Task Touch, Gigabit Ethernet, USB 2.0, 27.39 kg
 Lexmark CX410de. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200
 DPI, Print speed (colour, normal quality, A4/US Letter): 30 ppm. Copying: Colour copying, Maximum copy
 resolution: 1200 x 1200 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 1200 DPI.
 Faxing: Colour faxing. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, Grey



| Printing | | Paper handling | |
|---|-----------------------|------------------------------------|--|
| Print resolution colour | 1200 x 1200 DPI | Maximum print size | 216 x 356 mm |
| Print technology * | Laser | Paper tray media types * | Card stock, Labels, Plain paper, Transparencies |
| Printing * | Colour printing | ISO A-series sizes (A0...A9) * | A4, A5 |
| Duplex printing * | ✓ | Non-ISO print media sizes | Executive, Folio, Legal, Letter, Oficio |
| Maximum resolution * | 1200 x 1200 DPI | JIS B-series sizes (B0...B9) | B5 |
| Print speed (black, normal quality, A4/US Letter) * | 30 ppm | Paper tray media weight | 60 - 176 g/m ² |
| Print speed (colour, normal quality, A4/US Letter) | 30 ppm | Ports & interfaces | |
| Duplex print speed (black, normal quality, A4/US Letter) | 15 ppm | Standard interfaces | Ethernet, USB 2.0 |
| Duplex print speed (colour, normal quality, A4/US Letter) | 15 ppm | Direct printing * | ✓ |
| Time to first page (black, normal) | 10.5 s | USB port | ✓ |
| Time to first page (colour, normal) | 11.5 s | USB 2.0 ports quantity | 2 |
| Copying | | Optional connectivity | Wireless LAN |
| Duplex copying * | ✓ | Network | |
| Copying * | Colour copying | Wi-Fi * | ✗ |
| Maximum copy resolution * | 1200 x 1200 DPI | Ethernet LAN * | ✓ |
| Copy speed (black, normal quality, A4) | 30 cpm | Security algorithms | 802.1x RADIUS, EAP-TLS, EAP-TTLS, LEAP, MD5, PEAP |
| Copy speed (colour, normal quality, A4) | 30 cpm | Supported network protocols (IPv4) | TCP/IP, AppleTalk |
| Time to first copy (black, normal) | 10.8 s | Supported network protocols (IPv6) | TCP/IP, TCP, UDP |
| Time to first copy (colour, normal) | 11.6 s | Management protocols | HTTP, HTTPs (SSL*/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger |
| Copier resize | 25 - 400% | Network printing methods | LPR/LPD, Direct IP (9100), Enhanced IP (9400), FTP, TFTP, ThinPrint, Telnet, IPP 1.0, 1.1, 2.0 |
| N-in-1 copy function (N=) | 4 | Performance | |
| Scanning | | Maximum internal memory | 2560 MB |
| Duplex scanning * | ✓ | Card reader integrated | ✗ |
| Scanning * | Colour scanning | Internal memory * | 512 MB |
| Optical scanning resolution * | 600 x 1200 DPI | Processor frequency | 800 MHz |
| Maximum scan area | 216 x 356 mm | Sound pressure level (printing) | 49 dB |
| Scanner type * | Flatbed & ADF scanner | | |
| Scan technology | CCD | | |

| | | | |
|--|---|--|--|
| Scanning | | Performance | |
| Scan speed (colour) | 32 ppm | Sound pressure level (duplex printing) | 51 dB |
| Scan speed (black) | 32 ppm | Sound pressure level (copying) | 50 dB |
| Duplex scan speed (colour) | 14 ppm | Sound pressure level (scanning) | 50 dB |
| Duplex scan speed (black) | 14 ppm | Sound power level (standby) | 16 dB |
| Fax | | Design | |
| Duplex faxing | ✓ | Product colour * | Black, Grey |
| Faxing * | Colour faxing | Market positioning * | Business |
| Fax transmission speed | 3 sec/page | Display diagonal | 10.9 cm (4.3") |
| Modem speed | 33.6 Kbit/s | Touchscreen | ✓ |
| Features | | Control type | Touch |
| Recommended duty cycle | 800 - 6000 pages per month | System requirements | |
| Maximum duty cycle * | 75000 pages per month | Mac operating systems supported | Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion |
| Digital sender | ✗ | Linux operating systems supported | Fedora 14, Fedora 15, RedHat EL Linux 4.0 U5, RedHat EL Linux 4.0 U6, RedHat EL Linux 4.0 U7, RedHat EL Linux 5.0, RedHat EL Linux 5.1, RedHat EL Linux 5.2, RedHat EL Linux 5.3, SuSE Linux 10, SuSE Linux 10.2, SuSE Linux 10.3, SuSE Linux 11 |
| Number of print cartridges * | 5 | Server operating systems supported | Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64 |
| Printing colours * | Black, Cyan, Magenta, Yellow | Other operating systems supported | Novell NetWare 5.x, Novell NetWare 6.x, Novell Open Enterprise Server |
| Page description languages | Microsoft XPS, PCL 5c, PCL 6, PDF 1.7, PostScript 3, PPDS | Operational conditions | |
| Input & output capacity | | Operating relative humidity (H-H) | 8 - 80% |
| Total number of input trays * | 1 | Operating temperature (T-T) | 16 - 32 °C |
| Total input capacity * | 251 sheets | Operating altitude | 0 - 2896 m |
| Total output capacity * | 150 sheets | Sustainability | |
| Auto document feeder (ADF) | ✓ | Sustainability certificates | ENERGY STAR |
| Auto document feeder (ADF) input capacity | 50 sheets | Weight & dimensions | |
| Auto document feeder (ADF) output capacity | 50 sheets | Width | 444 mm |
| Maximum number of input trays | 4 | Depth | 558 mm |
| Maximum input capacity | 1451 sheets | Height | 470 mm |
| Maximum output capacity | 150 sheets | Weight | 27.4 kg |
| Paper handling | | Packaging data | |
| Maximum ISO A-series paper size * | A4 | Package width | 558 mm |
| | | Package depth | 594 mm |
| | | Package height | 567 mm |
| | | Package weight | 31.4 kg |
| | | Other features | |
| | | All-in-one functions | Copy, Fax, Print, Scan |
| | | Colour all-in-one functions | Copy, Fax, Print, Scan |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date