

# Lexmark MX331adn Laser A4 600 x 600 DPI 40 ppm

Brand : Lexmark

Product code: 29S0150

Product name : MX331adn

Monochrome Laser, 2.8", LCD , USB , RJ-45, 25 - 400 % , 6.2 s, Duplex, Dual Core, 1.0 GHz, 512 MB, 55 dBA

Lexmark MX331adn. Print technology: Laser, Printing: Mono printing, Maximum resolution: 600 x 600 DPI. Copying: Mono copying. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Maximum ISO A-series paper size: A4. Product colour: Black, White



Printing		Network	
Duplex printing mode	Auto	Ethernet LAN *	✓
Print technology *	Laser	Cabling technology	10/100/1000Base-T(X)
Printing *	Mono printing	Ethernet LAN data rates	10,1000 Mbit/s
Duplex printing *	✓	Security algorithms	LEAP, MD5, MSCHAPv2, PEAP, TLS, TTLS
Maximum resolution *	600 x 600 DPI	Supported network protocols (IPv4)	IPSEC, TCP/IP, ICMP, TCP, IGMP, UDP, 802.1x
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Supported network protocols (IPv6)	IPSEC, TCP/IP, ICMP, TCP, IGMP, UDP, 802.1x
Duplex print speed (black, normal quality, A4/US Letter)	17 ppm	Management protocols	DHCP, BOOTP, RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL/TLS), SMTP, Finger
Time to first page (black, normal)	6.2 s	Performance	
Copying		Maximum internal memory	512 MB
Duplex copying *	✓	Card reader integrated	✗
Duplex copying mode	Auto	Internal memory *	512 MB
Copying *	Mono copying	Built-in processor	✓
Copy speed (black, normal quality, A4)	40 cpm	Processor frequency	1000 MHz
Time to first copy (black, normal)	6.2 s	Processor cores	2
Copier resize	25 - 400%	Sound pressure level (printing)	53 dB
Scanning		Sound pressure level (copying)	54 dB
Duplex scanning *	✗	Sound pressure level (scanning)	55 dB
Scanning *	Colour scanning	Design	
Optical scanning resolution *	600 x 600 DPI	Product colour *	Black, White
Maximum scan area	215.9 x 355.6 mm	Market positioning *	Business
Scanner type *	Flatbed & ADF scanner	Built-in display *	✓
Scan technology	CIS	Display	LCD
Scan to	E-mail, FTP, HTTP, LDSS, USB	Display diagonal	7.11 cm (2.8")
Scan speed (colour)	22 ppm	Control type	Touch
Scan speed (black)	45 ppm	Power	
Image formats supported	JPEG, JPG, TIFF	Power consumption (printing)	530 W
Document formats supported	PDF, XPS	Power consumption (standby)	0.1 W
Fax		Power consumption (sleep)	0.8 W
Faxing *	Mono faxing	Energy Star Typical Electricity Consumption (TEC)	0.44 kWh/week
Fax transmission speed	3 sec/page	Features	
Modem speed	33.6 Kbit/s	Recommended duty cycle	500 - 5000 pages per month
		Maximum duty cycle *	50000 pages per month

Features		System requirements	
Number of print cartridges *	1	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Printing colours *	Black	Linux operating systems supported	Fedora 27, Linpus Linux 9.6, Ubuntu 16.04, Ubuntu 18.04 LTS, openSUSE 42.3
Page description languages	PCL 5c, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3	Server operating systems supported	SUSE Linux Enterprise Server, SUSE Linux Enterprise Server 12, Windows 2000 Server, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012
Country of origin	China	Other operating systems supported	Novell Open Enterprise Server 2
Input & output capacity		Operational conditions	
Total number of input trays *	2	Operating relative humidity (H-H)	8 - 80%
Total input capacity *	350 sheets	Operating temperature (T-T)	10 - 32 °C
Total output capacity *	150 sheets	Operating altitude	0 - 2896 m
Paper tray 1 input capacity	250 sheets	Certificates	
Multi-Purpose tray	✓	Certification ICES-003 B, BSMI B, US FDA, UL 60950-1, FCC B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECIP, CEL, C-tick DoC, UL-AR, KC, UL GS, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, DE-UZ 205, CGP	
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	50 sheets		
Maximum input capacity	900 sheets		
Maximum output capacity	150 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper		
ISO A-series sizes (A0...A9) *	A4, A5, A6		
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement		
Envelopes sizes	7 3/4, 9, 10, DL		
Paper tray media weight	60 - 120 g/m <sup>2</sup>		
Multi-Purpose Tray media weight	60 - 217 g/m <sup>2</sup>		
Ports & interfaces		Weight & dimensions	
Direct printing *	✗	Width	411 mm
USB port	✓	Depth	366 mm
USB connector	USB Type-A / USB Type-B	Height	339 mm
		Weight	12.8 kg
Network		Packaging data	
Wi-Fi *	✗	Package width	420 mm
		Package depth	465 mm
		Package height	385 mm
		Package weight	14.7 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	1500 pages
		Cables included	AC



0734646695664



734646695664

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.