

Lexmark CX921de Laser A3 1200 x 1200 DPI 35 ppm

Brand : Lexmark

Product code: 32CT065

Product name : CX921de

1200 x 1200 dpi, A3, CMY, 35 ppm, DADF, CCD, 33.6 Kbps, 2048 MB, 4x USB 2.0 A, RJ-45, USB 2.0 B, 51/53/55dB, LV TAA US

Lexmark CX921de. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200 DPI, Print speed (colour, normal quality, A4/US Letter): 35 ppm. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Maximum ISO A-series paper size: A3. Direct printing. Product colour: Black, White



Printing		Ports & interfaces	
Duplex printing mode	Auto	USB port	✓
Print technology *	Laser	Optional connectivity	Fiber, Parallel, Serial (RS-232), Wireless LAN
Printing *	Colour printing	Network	
Duplex printing *	✓	Wi-Fi *	✗
Maximum resolution *	1200 x 1200 DPI	Ethernet LAN *	✓
Print speed (black, normal quality, A4/US Letter) *	35 ppm	Cabling technology	10/100/1000Base-T(X)
Print speed (colour, normal quality, A4/US Letter)	35 ppm	Ethernet LAN data rates	10,100,1000 Mbit/s
Duplex print speed (black, normal quality, A4/US Letter)	35 ppm	Security algorithms	IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, TTLS
Time to first page (black, normal)	6.8 s	Mobile printing technologies	Apple AirPrint, Google Cloud Print, Mopria Print Service
Time to first page (colour, normal)	6.8 s	Performance	
Copying		Maximum internal memory	4096 MB
Copying *	Colour copying	Card reader integrated	✗
Copy speed (black, normal quality, A4)	35 cpm	Internal memory *	2048 MB
Copy speed (colour, normal quality, A4)	35 cpm	Built-in processor	✓
Duplex copy speed (black, US Letter)	160 ppm	Processor frequency	1200 MHz
Time to first copy (black, normal)	6.6 s	Processor cores	4
Time to first copy (colour, normal)	7.9 s	Sound pressure level (printing)	51 dB
Copier resize	25 - 400%	Sound pressure level (duplex printing)	53 dB
Scanning		Sound pressure level (copying)	55 dB
Duplex scanning *	✓	Sound pressure level (scanning)	53 dB
Scanning *	Colour scanning	Design	
Optical scanning resolution *	600 x 600 DPI	Product colour *	Black, White
Maximum scan area	297 x 432 mm	Market positioning *	Business
Scanner type *	Flatbed & ADF scanner	Built-in display *	✓
Scan technology	CCD	Display	LCD
Scan to	E-mail, FTP, USB	Display diagonal	25.4 cm (10")
Scan speed (colour)	80 ppm	Touchscreen	✓
Scan speed (black)	80 ppm	Control type	Touch
Duplex scan speed (colour)	160 ppm	Colour display	✓
Duplex scan speed (black)	160 ppm	Power	
Image formats supported	JPG, TIF	Power consumption (printing)	675 W
Document formats supported	PDF, XPS	Power consumption (copying)	700 W
Fax		Power consumption (scanning)	230 W
Faxing *	Mono faxing	Power consumption (ready)	220 W
Fax transmission speed	3 sec/page	Power consumption (sleep)	2.9 W
Modem speed	33.6 Kbit/s	Energy Star Typical Electricity Consumption (TEC)	2.3 kWh/week

Features		Power	
Recommended duty cycle	4000 - 20000 pages per month	AC input voltage	110 V
Maximum duty cycle *	200000 pages per month	System requirements	
Printing colours *	Cyan, Magenta, Yellow	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Input & output capacity		Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Total number of input trays *	2	Linux operating systems supported	Debian 7.0, Debian 8.0, Fedora 21, Fedora 22, Linpus Lite 2.1, Linux Mint 13, Linux Mint 17, Linux Mint 17.1, Linux Mint 17.2, Linux Mint Debian Edition 2 (LMDE 2), Red Hat Enterprise Linux WS 4.0, Red Hat Enterprise Linux WS 5.0, Red Hat Enterprise Linux WS 6.0, Red Hat Enterprise Linux WS 7.0, SUSE Linux Enterprise Desktop 10, SUSE Linux Enterprise Desktop 11, SUSE Linux Enterprise Desktop 12, SuSE Linux 10, SuSE Linux 11, SuSE Linux 12.0, Ubuntu 12.04, Ubuntu 14.04, Ubuntu 15.04, openSUSE 13.1, openSUSE 13.2, openSUSE Tumbleweed
Total input capacity *	1150 sheets	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64, Windows Server 2012, Windows Server 2012 R2
Total output capacity *	250 sheets	Operational conditions	
Multi-Purpose tray	✓	Operating relative humidity (H-H)	15 - 85%
Multi-Purpose tray input capacity	150 sheets	Operating temperature (T-T)	10 - 30 °C
Auto document feeder (ADF)	✓	Operating altitude	0 - 2500 m
Auto document feeder (ADF) input capacity	100 sheets	Certificates	
Maximum number of input trays	5	Certification	ICES-003 A, BSMI A, VCCI A, FCC A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB, ISO-532B, CE (EU) DoC, EFTA (CE), KC, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT
Maximum input capacity	6650 sheets	Sustainability	
Maximum output capacity	3500 sheets	Sustainability certificates	Blue Angel, ENERGY STAR
Paper handling		Weight & dimensions	
Maximum ISO A-series paper size *	A3	Width	615 mm
Paper tray media types *	Banner, Card stock, Envelopes, Labels, Plain paper	Depth	697 mm
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6	Height	921 mm
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Weight	108.5 kg
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Packaging data	
Paper tray media weight	60 - 256 g/m ²	Package width	758 mm
Multi-Purpose Tray media weight	60 - 256 g/m ²	Package depth	911 mm
Ports & interfaces		Package height	1247 mm
Standard interfaces	Ethernet, USB 2.0	Package weight	133 kg
Direct printing *	✓	Other features	
		Finishing option	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date