

## Lexmark MS415dn 1200 x 1200 DPI A4

**Brand :** Lexmark

**Product code:** 3550260

**Product name :** MS415dn

Mono, Duplex, 40 ppm, 300 Pages In (Standard), Dual Core CPU 800 MHz, 256MB, 2.4" LCD

[Lexmark MS415dn 1200 x 1200 DPI A4:](#)

### Elevated performance and big-business features

The Lexmark MS415dn combines a powerful processor, 256 MB of memory, 2.4-inch (6 cm) color display, eco-conscious features, and output at up to 40 pages per minute.

Lexmark MS415dn. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 80000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 40 ppm, Duplex printing. Display: LCD. Network ready. Product colour: Black, White



Printing		Performance	
Duplex printing mode	Auto/Manual	Internal memory *	256 MB
Colour *	✗	Maximum internal memory	256 MB
Print technology *	Laser	Card reader integrated	✗
Duplex printing *	✓	Built-in processor	✓
Maximum resolution *	1200 x 1200 DPI	Processor model	2-Core
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Processor frequency	800 MHz
Duplex print speed (black, normal quality, A4/US Letter)	18 ppm	Sound pressure level (printing)	54 dB
Time to first page (black, normal)	6.5 s	Sound pressure level (duplex printing)	54 dB
		Noise level (idle)	15 dB
Features		Design	
Maximum duty cycle *	80000 pages per month	Product colour *	Black, White
Recommended duty cycle	750 - 7200 pages per month	Built-in display *	✓
Printing colours *	Black	Display	LCD
Number of print cartridges *	1	Display diagonal	6.1 cm (2.4")
Page description languages *	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PostScript 3, PPDS	Touchscreen	✗
Input & output capacity			ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER
Total number of input trays *	2	Certification	
Total input capacity *	300 sheets		
Total output capacity *	150 sheets		
Paper input type	Paper tray		
Multi-Purpose tray	✓		
Multi-Purpose tray input capacity	50 sheets		
Maximum number of input trays	3		
Maximum input capacity	850 sheets		
Maximum output capacity	150 sheets		
Paper handling		Power	
Maximum ISO A-series paper size *	A4	Power consumption (printing) *	560 W
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	System requirements	
ISO A-series sizes (A0...A9) *	A4, A5, A6	Windows operating systems supported	✓
		Mac operating systems supported	✓

Paper handling		System requirements	
Non-ISO print media sizes	Executive, Folio, Letter, Oficio, Statement, Universal, Legal	Linux operating systems supported	✓
Paper tray media weight (imperial)	7.26 - 10.9 kg (16 - 24 lbs)	Server operating systems supported	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64, Windows Server 2012, Windows Server 2012 R2
Multi-Purpose Tray media weight (imperial)	7.26 - 19.5 kg (16 - 43 lbs)	Other operating systems supported	✓
Ports & interfaces		Operational conditions	
Standard interfaces	Ethernet, Parallel, USB 2.0	Operating temperature (T-T)	16 - 32 °C
Direct printing *	✗	Operating relative humidity (H-H)	8 - 80%
USB 2.0 ports quantity	1	Operating altitude	0 - 2896 m
Optional connectivity	Wireless LAN	Sustainability	
Network		Sustainability certificates	ENERGY STAR
Network ready	✓	Weight & dimensions	
Ethernet LAN *	✓	Width	400 mm
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Depth	381 mm
Security algorithms	802.1x RADIUS, HTTPS, LEAP, MD5, PEAP, SSL/TLS	Height	261.6 mm
Supported network protocols (IPv4)	TCP/IP IPv4, AppleTalk	Weight	14.2 kg
Supported network protocols (IPv6)	TCP/IP IPv6, TCP, UDP	Packaging data	
Management protocols	HTTP HTTPS (SSL/TLS) SNMPv1, SNMPv2c SNMPv3 WINS IGMP APIPA (AutoIP) DHCP ICMP DNS Bonjour DDNS mDNS ARP NTP Telnet Finger	Package width	431.8 mm
Mobile printing technologies	Apple AirPrint	Package depth	472 mm
		Package height	381 mm
		Package weight	16 kg
		Other features	
		Power LED	✓



0734646525398



734646525398

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.