

Lexmark MS310dn 1200 x 1200 DPI A4

Brand : Lexmark

Product code: 35ST301

Product name : MS310dn

Laser, 1200 x 1200 dpi, 33 ppm, Ethernet, USB 2.0, 14 kg

[Lexmark MS310dn 1200 x 1200 DPI A4:](#)

Convenient Printing. Compact Design.

The Lexmark MS310dn network-ready laser printer with internal two-sided printing, an 800 MHz dual-core processor, 128MB of standard memory, 300-sheet standard input and a print speed of up to 33 ppm quickly and easily performs tasks.

Print Complex Documents Fast

With 128 MB of memory and a powerful 800 MHz dual-core processor, it prints documents with graphics and images effortlessly.

Reliable Performance

Easily print up to 2,500 pages per month, plus enjoy fewer maintenance hassles, thanks to our state of the art paper handling.

Run Jobs without Interruption

With an input capacity of up to 850 sheets means you won't have to add paper as often.

Get Work Done Quickly

Enjoy print speeds of up to 33 pages per minute and your first page printed in as little as 6.5 seconds.

Fast Set Up

Instructions are easy. You'll be up and running in minutes.



Printing		Network	
Colour *	✗	Supported network protocols (IPv6)	TCP/IP IPv6, TCP, UDP
Print technology *	Laser		HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger
Duplex printing *	✓	Management protocols	
Maximum resolution *	1200 x 1200 DPI	Performance	
Print speed (black, normal quality, A4/US Letter) *	33 ppm	Internal memory *	128 MB
Duplex print speed (black, normal quality, A4/US Letter)	14 ppm	Maximum internal memory	128 MB
Time to first page (black, normal)	6.5 s	Processor frequency	800 MHz
Features		Sound pressure level (printing)	53 dB
Maximum duty cycle *	50000 pages per month	Sound pressure level (duplex printing)	52 dB
Recommended duty cycle	500 - 2500 pages per month	Sound power level (standby)	15 dB
Printing colours *	Black	Design	
Number of print cartridges *	1	Product colour *	Black, Grey
Page description languages *	Microsoft XPS, PCL 5e, PCL 6, PostScript 3	System requirements	
Input & output capacity		Windows operating systems supported	✓
Total number of input trays *	2	Mac operating systems supported	✓
Total input capacity *	300 sheets	Linux operating systems supported	✓
Total output capacity *	150 sheets	Server operating systems supported	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64
Maximum number of input trays	3	Operational conditions	
Maximum input capacity	850 sheets	Operating temperature (T-T)	16 - 32 °C
Maximum output capacity	150 sheets	Storage temperature (T-T)	-10 - 43 °C
Paper handling		Operating relative humidity (H-H)	8 - 80%
Maximum ISO A-series paper size *	A4	Storage relative humidity (H-H)	10 - 90%
Maximum print size	216 x 356 mm		
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies		
ISO A-series sizes (A0...A9) *	A4, A5, A6		

Paper handling		Operational conditions	
Non-ISO print media sizes	Executive, Folio, Letter, Oficio, Statement, Legal	Operating altitude	0 - 2896 m
Envelopes sizes	7 3/4, 9, 10, DL	Sustainability	
Paper tray media weight	60 - 90 g/m ²	Sustainability certificates	Blue Angel, ENERGY STAR
Ports & interfaces		Weight & dimensions	
Standard interfaces	Ethernet, Parallel, USB 2.0	Width	399 mm
Direct printing *	✘	Depth	382 mm
USB 2.0 ports quantity	1	Height	263 mm
Optional connectivity	Wireless LAN	Weight	14 kg
Network		Packaging data	
Network ready	✔	Package width	432 mm
Wi-Fi *	✘	Package depth	472 mm
Ethernet LAN *	✔	Package height	380 mm
Security algorithms	802.1x RADIUS, EAP-TLS, EAP-TTLS, LEAP, MD5, PEAP	Package weight	15.8 kg
Supported network protocols (IPv4)	TCP/IP IPv4, AppleTalk	Other features	
		Power LED	✔
		Stand-by LED	✔

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date