

Lexmark MB2546adwe Laser A4 1200 x 1200 DPI 46 ppm Wi-Fi

Brand : Lexmark

Product code: 36SC871

Product name : MB2546adwe

- Monochrome Laser
 - Duplex (2-sided) Printing: Integrated Duplex
 - Print Speed: 46 ppm
 - Recommended Monthly Page Volume: 2000 - 15000 pages
 MB2546adwe, 46 ppm, 1.9 KW/h, 56 dB, 1 GHz, 1024 MB, Gigabit Ethernet, 802.11bgn, RJ - 45, USB 2.0, 477.52 x 490.22 x 429.26 mm, 20.6 kg
 Lexmark MB2546adwe. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying. Scanning: Colour scanning. Faxing: Mono faxing. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: Black, Grey



Printing		Network	
Print technology *	Laser	Cabling technology	10/100/1000Base-T(X)
Printing *	Mono printing	Ethernet LAN data rates	10,100,1000 Mbit/s
Duplex printing *	✓	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Maximum resolution *	1200 x 1200 DPI	Security algorithms	802.1x RADIUS, IPsec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, TTLS
Print speed (black, normal quality, A4/US Letter) *	46 ppm	Management protocols	DHCP, AIPPA (AutoIP), BOOTP, RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL/TLS), Finger
Duplex print speed (black, normal quality, A4/US Letter)	23 ppm	Mobile printing technologies	Apple AirPrint
Time to first page (black, normal)	6 s		
Print margins (top, bottom, right, left)	3.99 mm		
Copying		Performance	
Duplex copying *	✓	Maximum internal memory	1024 MB
Copying *	Mono copying	Card reader integrated	✗
Copy speed (black, normal, US Letter)	46 cpm	Internal memory *	1024 MB
Duplex copy speed (black, US Letter)	23 ppm	Built-in processor	✓
Time to first copy (black, normal)	6 s	Processor frequency	1000 MHz
Copier resize	25 - 400%	Processor cores	2
Scanning		Sound pressure level (printing)	56 dB
Duplex scanning *	✓	Sound pressure level (duplex printing)	55 dB
Scanning *	Colour scanning	Sound pressure level (copying)	56 dB
Optical scanning resolution (black)	1200 x 600 ppi	Sound pressure level (scanning)	55 dB
Optical scanning resolution (colour)	600 x 600 ppi		
Maximum scan area	251.9 x 355.6 mm	Design	
Scanner type *	Flatbed & ADF scanner	Product colour *	Black, Grey
Scan technology	CIS	Market positioning *	Business
Scan to	E-mail, FTP, PC, USB	Built-in display *	✓
Scan speed (colour)	22 ppm	Display diagonal	10.9 cm (4.3")
Scan speed (black)	45 ppm	Touchscreen	✓
Duplex scan speed (colour)	10.5 ppm	Control type	Touch
Duplex scan speed (black)	20 ppm	Colour display	✓
Image formats supported	JPEG, JPG, TIFF	Power	
Document formats supported	PDF, XPS	Power consumption (printing)	620 W
Fax		Power consumption (copying)	630 W
Faxing *	Mono faxing	Power consumption (scanning)	20 W
Fax transmission speed	3 sec/page	Power consumption (ready)	14.5 W
Modem speed	33.6 Kbit/s	Power consumption (standby)	2.6 W
		Energy Star Typical Electricity Consumption (TEC)	1.9 kWh/week
Features			
Recommended duty cycle	2000 - 15000 pages per month		

Features		System requirements	
Maximum duty cycle *	120000 pages per month	Windows operating systems supported	Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64
Printing colours *	Black		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
Page description languages	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3		Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Country of origin	China		Debian 7.0, Debian 8.0, Fedora 23, Red Hat Enterprise Linux WS 6.0, Red Hat Enterprise Linux WS 7.0, Ubuntu 16.04, openSUSE 13.2
Input & output capacity		Mac operating systems supported	
Total number of input trays *	2	Linux operating systems supported	SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, SUSE Linux Enterprise Server 12, Windows 2000 Server, Windows Server 2012
Total input capacity *	350 sheets		IBM AIX 6.1, Novell NetWare 5.x, Novell NetWare 6.x, Novell Open Enterprise Server, Solaris 10, Solaris 10 SPARC, Solaris 11, Solaris 11 SPARC
Total output capacity *	150 sheets		
Multi-Purpose tray	✓		
Multi-Purpose tray input capacity	100 sheets	Server operating systems supported	
Paper input type	Paper tray		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	50 sheets		
Maximum number of input trays	5	Other operating systems supported	
Maximum input capacity	2000 sheets		
Maximum output capacity	150 sheets		
Paper handling		Operational conditions	
Maximum ISO A-series paper size *	A4	Operating relative humidity (H-H)	8 - 80%
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Operating temperature (T-T)	10 - 32 °C
ISO A-series sizes (A0...A9) *	A4, A5, A6	Operating altitude	0 - 5000 m
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Certificates	
Envelopes sizes	7 3/4, 9, 10, DL	Certification	ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER
Paper tray media weight	60 - 120 g/m ²		
Ports & interfaces			
Standard interfaces	Ethernet, USB 2.0, Wireless LAN		
Direct printing *	✓	Sustainability	
USB port	✓	Sustainability certificates	EPEAT Silver, ENERGY STAR
USB connector	USB Type-A / USB Type-B	Weight & dimensions	
USB 2.0 ports quantity	3	Width	490.2 mm
Optional connectivity	Parallel, Serial (RS-232)	Depth	429.3 mm
Network		Height	477.5 mm
Wi-Fi *	✓	Weight	20.6 kg
Ethernet LAN *	✓	Packaging data	
		Package width	511.1 mm
		Package depth	576.1 mm
		Package height	613.9 mm
		Package weight	23.7 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	3000 pages
		Imaging unit included	✓
		Power cord included	✓
		Other features	
		Safety sheet	✓
		Software CD	✓
		Documentation CD	✓



0734646680530



734646680530

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.