



DELL 406-BBGR network card Internal Fiber 8192 Mbit/s

Brand : DELL


Product code: 406-BBGR

Product name : 406-BBGR

2 x 8GFC LC (MM), PCI-e

DELL 406-BBGR. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Fiber.

Maximum data transfer rate: 8192 Mbit/s. Product colour: Green



Ports & interfaces		Design	
Connectivity technology *	Wired		PowerEdge 1950 PowerEdge 2970
Host interface *	PCI Express		PowerEdge R220 PowerEdge R310
Interface *	Fiber		PowerEdge R320 PowerEdge R410
Fiber ports quantity	2		PowerEdge R415 PowerEdge R420
Fiber optic connector	LC		PowerEdge R430 PowerEdge R510
PCI version	2.0		PowerEdge R515 PowerEdge R520
PCI Card form factor	Half-height (low-profile)		PowerEdge R530 PowerEdge R610
			PowerEdge R620 PowerEdge R630
			PowerEdge R710 PowerEdge R715
			PowerEdge R720 PowerEdge R720XD
			PowerEdge R730
			PowerEdge R730XD PowerEdge R805
			PowerEdge R810 PowerEdge R815
			PowerEdge R820 PowerEdge R900
			PowerEdge R905 PowerEdge R910
			PowerEdge R920 PowerEdge T410
			PowerEdge T420 PowerEdge T430
			PowerEdge T610 PowerEdge T620
			PowerEdge T630 PowerEdge T710
			PowerEdge VRTX PowerVault DL2000
			PowerVault DL2200
Network		Compatible products	
Maximum data transfer rate *	8192 Mbit/s		
Networking standards *	IEEE 802.3ae		
Ethernet LAN	✓		
Ethernet LAN data rates	10000 Mbit/s		
Copper ethernet cabling technology	10GBASE-T		
Fiber ethernet cabling technology	10GBASE-ER, 10GBASE-EW, 10GBASE-LR, 10GBASE-LW, 10GBASE-SR, 10GBASE-SW		
Design		System requirements	
Component for *	Server		Windows Vista Business, Windows Vista Enterprise, Windows Vista Home Basic, Windows Vista Home Premium, Windows Vista Ultimate
Product colour	Green	Windows operating systems supported	
Internal *	✓	Server operating systems supported	Windows Server 2003, Windows Server 2008
Certification	CISPR 22 Class A, DHHS, EN55022 Class A, EMC, ICES-003 Class A, UL 60950-1, EN 60950-1, CSA C22.2 No. 60950-1-03, FCC Part 15 A, EN 60825-1, EN55024 Class A, BSMI Class A, VCCI Class A		
Operational conditions			
		Operating temperature (T-T)	0 - 55 °C
		Operating relative humidity (H-H)	5 - 95%
Sustainability			
		Sustainability certificates	RoHS
Weight & dimensions			
		Depth	167.6 mm
		Height	68.9 mm
Logistics data			
		Harmonized System (HS) code	85176990



5397063818334

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.