



# Lenovo ThinkPad USB 3.0 Pro Dock Wired USB 3.2 Gen 1 (3.1 Gen 1) Type-A Black

**Brand :** Lenovo

**Product code:** 40A70045US

**Product name :** ThinkPad USB 3.0 Pro Dock



ThinkPad USB 3.0 Pro Dock, 236g, Black

[Lenovo ThinkPad USB 3.0 Pro Dock Wired USB 3.2 Gen 1 \(3.1 Gen 1\) Type-A Black:](#)

The ThinkPad USB 3.0 Pro Dock delivers a professional universal USB docking solution with fast USB 3.0 ports and digital video ports for quick and easy connection to all the workspace peripherals you use every day. Simply plug in a single USB 3.0 cable into your Lenovo PC for instant access to up to two external monitors, Gigabit Ethernet, headphones/speakers, USB printers, scanners, keyboard, mouse and so on for daily use. The Dock can also charge your mobile device via USB always power on port. **Lenovo ThinkPad USB 3.0 Pro Dock. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, Headphone connectivity: 3.5 mm. Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Black, Certification: FCC/ICES CE KCC RCM BSMI VCCI CB UL+cUL EAC TUV Mark Serbia Kvalitet South Africa.... Power source type: AC, Power consumption (typical): 45 W, Compatible power plug types: US. Width: 150 mm, Depth: 80 mm, Height: 32 mm**

Ports & interfaces		Power	
Connectivity technology *	Wired	Power source type	AC
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Power consumption (typical)	45 W
USB 2.0 ports quantity *	2	Compatible power plug types	US
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	<b>Operational conditions</b>	
DisplayPorts quantity	1	Operating temperature (T-T)	5 - 40 °C
DVI-I ports quantity	1	Operating relative humidity (H-H)	20 - 95%
Microphone in *	✗	<b>Weight &amp; dimensions</b>	
Combo headphone/mic port	✓	Width	150 mm
Headphone connectivity	3.5 mm	Depth	80 mm
<b>Network</b>		Height	32 mm
Ethernet LAN *	✓	Weight	236 g
Ethernet LAN (RJ-45) ports	1	<b>Packaging data</b>	
Ethernet LAN data rates	10,100,1000 Mbit/s	Package width	214 mm
<b>Performance</b>		Package depth	182 mm
Card reader integrated *	✗	Package height	64 mm
Cable lock slot	✓	Package weight	777 g
Product colour *	Black	<b>Packaging content</b>	
Certification	FCC/ICES CE KCC RCM BSMI VCCI CB UL+cUL EAC TUV Mark Serbia Kvalitet South Africa SABS&LoA Israel SII Ukraine DoC	Cables included	AC, USB
		AC adapter included	✓
		Interface adapters included	DVI-I male - VGA female



0889561429747



889561429747

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.