




Lenovo Intel Xeon E5-2660 v4 processor 2 GHz 35 MB L3

Brand : Lenovo

Product code: 4XG0G89058

Product name : Intel Xeon E5-2660 v4

Intel Xeon E5-2660 v4, 35M Cache, 2 GHz, 9.6 GT/s QPI, Factory Integrated
Lenovo Intel Xeon E5-2660 v4. Processor family: Intel® Xeon® E5 v4, Processor socket: LGA 2011-v3, Processor lithography: 14 nm. Memory channels: Quad-channel, Memory types supported by processor: DDR4-SDRAM, Memory clock speeds supported by processor: 1600,1866,2133,2400 MHz. Market segment: Server, Supported instruction sets: AVX 2.0, Scalability: 2S



Processor		Features	
Processor model *	E5-2660V4	Supported instruction sets	AVX 2.0
Processor base frequency *	2 GHz	Scalability	2S
Processor family *	Intel® Xeon® E5 v4	Physical Address Extension (PAE)	✓
Processor cores *	14	CPU configuration (max)	2
Processor socket *	LGA 2011-v3	Embedded options available	✗
Component for	Server/workstation	Physical Address Extension (PAE)	46 bit
Processor lithography *	14 nm	Processor special features	
Processor series	Intel Xeon E5-2600 v4	Intel® Hyper Threading Technology (Intel® HT Technology)	✓
Processor threads	28	Intel® Identity Protection Technology (Intel® IPT)	✗
System bus rate	9.6 GT/s	Intel® Turbo Boost Technology	2.0
Processor operating modes *	64-bit	Intel Flex Memory Access	✗
Processor boost frequency	3.2 GHz	Intel® AES New Instructions (Intel® AES-NI)	✓
Processor cache	35 MB	Enhanced Intel SpeedStep Technology	✓
Processor cache type	L3	Intel Trusted Execution Technology	✓
Thermal Design Power (TDP)	105 W	Intel VT-x with Extended Page Tables (EPT)	✓
Stepping	M0	Intel Demand Based Switching	✓
Bus type	QPI	Intel® Secure Key	✓
Number of QPI links	2	Intel TSX-NI	✓
Memory bandwidth supported by processor (max)	76.8 GB/s	Intel® OS Guard	✓
Memory		Intel 64	✓
Memory types supported by processor	DDR4-SDRAM	Intel Virtualization Technology (VT-x)	✓
Memory clock speeds supported by processor	1600,1866,2133,2400 MHz	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Memory channels *	Quad-channel	Conflict-Free processor	✓
ECC	✓	Intel® vPro™ Platform Eligibility	✓
Graphics		Operational conditions	
On-board graphics card *	✗	Tcase	79 °C
Features			
Execute Disable Bit	✓		
Idle States	✓		
Thermal Monitoring Technologies	✓		
Market segment	Server		
Maximum number of PCI Express lanes	40		
PCI Express slots version	3.0		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-JAN-2024. Prints or copies of Information are only valid on the printed Publication date