




## Lenovo 7Y37A01091 interface cards/adapters Internal SAS, SATA

**Brand :** Lenovo

**Product code:** 7Y37A01091

**Product name :** 7Y37A01091



ThinkSystem 430-16e SAS/SATA 12Gb HBA

[Lenovo 7Y37A01091 interface cards/adapters Internal SAS, SATA:](#)

The Lenovo ThinkSystem 430-8e and 430-16e SAS/SATA 12Gb HBAs are high performance host bus adapters for external storage connectivity in ThinkSystem servers. The 430-8e provides two x4 external mini-SAS HD connectors with eight lanes of 12 Gbps SAS. The 430-16e provides four x4 external mini-SAS HD connectors with 16 lanes of 12 Gbps SAS.



This product guide provides essential presales information to understand the ThinkSystem external HBAs and their key features, specifications, and compatibility. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the HBAs and consider their use in IT solutions.

Ports & interfaces		Operational conditions	
Host interface *	PCIe	Storage temperature (T-T)	-40 - 70 °C
Output interface *	SAS, SATA	Operating relative humidity (H-H)	20 - 90%
Expansion card form factor	Full-height / Low-profile	Storage relative humidity (H-H)	5 - 95%
Expansion card standard	PCIe 3.0		
External mini-SAS HD ports	4		
Design		Technical details	
Internal *	✓	Sustainability certificates	RoHS
Product colour	Black, Green	Logistics data	
Certification	FCC Part 15 Class A Australia/New Zealand (AS/NZS CISPR 22) Canada (ICES-003 Class B) Europe (EN55022/EN55024) Japan (VCCI V-3) Korea (RRA no 2013-24 & 25) WEEE EN/IEC/UL 60950 Taiwan (CNS 13438) USA (FCC 47 CFR part 15 Subpart B class B)	Harmonized System (HS) code	84733020
Features		Other features	
Data transfer rate (max)	12000 Gbit/s	Compatible operating systems	Microsoft Windows Server 2012 R2 Microsoft Windows Server 2016 Red Hat Enterprise Linux 6 Server x64 Edition Red Hat Enterprise Linux 7 SUSE Linux Enterprise Server 11 for AMD64/EM64T SUSE Linux Enterprise Server 11 with Xen for AMD64/EM64T SUSE Linux Enterprise Server 12 SUSE Linux Enterprise Server 12 with XEN VMware vSphere ESXi 6.0 VMware vSphere ESXi 6.5
Operational conditions		Compatibility	SR530, SR550, SR570, SR590, SR630, SR650, SR850, SR860, SR950, SD530
Operating temperature (T-T)	10 - 55 °C		



0889488433520



889488433520

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.