



Lenovo ThinkSystem DE4000H disk array Rack (2U) Black



Brand : Lenovo

Product code: 7Y75A00TWW

Product name : ThinkSystem DE4000H

ThinkSystem DE4000H - 2U24 - 2x Gen2 controllers

[Lenovo ThinkSystem DE4000H disk array Rack \(2U\) Black:](#)

Lenovo ThinkSystem DE4000H is a scalable, hybrid entry-level storage system that is designed to provide performance, simplicity, capacity, security, and high availability for medium to large businesses. The ThinkSystem DE4000H delivers enterprise-class storage management capabilities with a wide choice of host connectivity options, flexible drive configurations, and enhanced data management features.

This product guide provides essential technical and pre-sales information on the Lenovo ThinkSystem DE4000H Hybrid Storage Array, its key features and specifications, components and options, and configuration guidelines.

This guide is intended for technical specialists, sales specialists, sales engineers, and IT architects who want to learn more about the ThinkSystem DE4000H Hybrid Storage Array and consider its use in their solutions.

Storage		Design				
Storage drives installed *	✗	Certification	United States: FCC Part 15, Class A; UL 60950-1 and 62368-1 Canada: ICES-003, Class A; CAN/CSA-C22.2 60950-1 and 62368-1 Argentina: IEC60950-1 Mexico NOM European Union: CE Mark (EN55032 Class A, EN55024, IEC/EN60950-1 and 62368-1); ROHS Directive 2011/65/EU Russia, Kazakhstan, Belarus: EAC China: CCC GB 4943.1, GB 17625.1, GB 9254 Class A; CELP; CECP India: BIS Japan: VCCI, Class A Taiwan: BSMI CNS 13438, Class A; CNS 14336-1 Korea KN32/35, Class A Australia/New Zealand: AS/NZS CISPR 22 Class A			
Installed storage drive type *	✗					
Supported storage drive types *	HDD & SSD					
Number of storage drives supported *	24					
Maximum supported storage capacity *	288 TB					
RAID levels	0, 1, 3, 5, 6, 10					
Hot-swap drive bays	✓					
Ports & interfaces		Performance	Large Enterprise Business			
USB connectivity *	✓					
Serial interface type	RJ-45					
RJ-45 ports quantity	3	Power	913 W			
Design	Chassis type *			Rack (2U)	Number of power supply units	2
	Product colour			Black	AC input voltage	100 - 240 V
	LED indicators	✓	Weight & dimensions	24.6 kg		
	Cooling	✓			Width	449 mm
Built-in display	✓	Depth			553 mm	
Operational conditions			Height	85 mm		
			Operating temperature (T-T)	5 - 45 °C		
			Operating relative humidity (H-H)	8 - 90%		
			Storage temperature (T-T)	-10 - 50 °C		
			Storage relative humidity (H-H)	10 - 90%		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-JAN-2024. Prints or copies of Information are only valid on the printed Publication date