



Lenovo System x3650 M5 server Rack (2U) Intel® Xeon® E5 v4 E5-2640V4 2.4 GHz 16 GB DDR4-SDRAM 900 W

Brand : Lenovo

Product family: System


Product code: 8871KKU

Product name : x3650 M5



1x E5-2640 v4 10C 2.4GHz 25MB 2133MHz 90W, 1x 16GB DDR4, RAID M5210, 8x 3.5" HS, 4x GbE, Included, 1x 900W HS

Lenovo System x3650 M5. Processor family: Intel® Xeon® E5 v4, Processor frequency: 2.4 GHz, Processor model: E5-2640V4. Internal memory: 16 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 16 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 900 W, Redundant power supply (RPS) support. Chassis type: Rack (2U)



Processor		Ports & interfaces	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Processor family *	Intel® Xeon® E5 v4	VGA (D-Sub) ports quantity	1
Processor model *	E5-2640V4	Expansion slots	
Processor frequency *	2.4 GHz	PCI Express x8 (Gen 3.x) slots	8
Processor boost frequency	3.4 GHz	PCI Express slots version	3.0
Processor cores	10	Design	
Processor cache	25 MB	Chassis type *	Rack (2U)
Memory channels supported by processor	Quad	Rack mounting	✓
Number of processors installed	1	Redundant fans support	✓
Thermal Design Power (TDP)	90 W	Rack rails	✓
Processor cache type	Smart Cache	Performance	
System bus rate	8 GT/s	Trusted Platform Module (TPM)	✓
Processor socket	LGA 2011-v3	On-site support	✓
Processor lithography	14 nm	Trusted Platform Module (TPM) version	2.0
Processor threads	20	Software	
Processor operating modes	64-bit	Operating system installed *	✗
Stepping	R0	Compatible operating systems *	Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSphere
Bus type	QPI	Processor special features	
Number of QPI links	2	CPU configuration (max)	2
Processor codename	Broadwell	Enhanced Intel SpeedStep Technology	✓
Tcase	76 °C	Intel® Identity Protection Technology (Intel® IPT)	✗
Maximum internal memory supported by processor	1.54 TB	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Memory types supported by processor	DDR4-SDRAM	Intel® Hyper Threading Technology (Intel® HT Technology)	✓
Memory clock speeds supported by processor	1600,1866,2133 MHz	Intel® Turbo Boost Technology	2.0
Memory bandwidth supported by processor (max)	68.3 GB/s	Intel Flex Memory Access	✗
ECC supported by processor	✓	Intel® AES New Instructions (Intel® AES-NI)	✓
Execute Disable Bit	✓	Intel Trusted Execution Technology	✓
Idle States	✓		
Thermal Monitoring Technologies	✓		
Maximum number of PCI Express lanes	40		
PCI Express configurations	1x4, 1x8, 1x16		

Processor		Processor special features	
Processor package size	52.5 x 51 mm	Intel VT-x with Extended Page Tables (EPT)	✓
Supported instruction sets	AVX 2.0	Intel Demand Based Switching	✓
Scalability	2S	Intel® Secure Key	✓
Physical Address Extension (PAE)	✓	Intel TSX-NI	✓
Physical Address Extension (PAE)	46 bit	Intel® OS Guard	✓
Embedded options available	✓	Intel 64	✓
Processor series	Intel Xeon E5-2600 v4	Intel Virtualization Technology (VT-x)	✓
Conflict-Free processor	✓	Processor ARK ID	92984
Memory		Power	
Internal memory *	16 GB	Redundant power supply (RPS) support *	✓
Internal memory type *	DDR4-SDRAM	Power supply *	900 W
Memory slots	24	Operational conditions	
Memory layout (slots x size)	1 x 16 GB	Operating temperature (T-T)	5 - 40 °C
Maximum internal memory *	1.54 TB	Storage temperature (T-T)	5 - 45 °C
Storage		Operating relative humidity (H-H)	8 - 85%
Maximum storage capacity *	147.6 TB	Storage relative humidity (H-H)	8 - 85%
RAID support *	✓	Operating altitude	0 - 3050 m
Hot-Plug support	✓	Weight & dimensions	
Hot-swap	✓	Width	446 mm
Optical drive type *	✗	Depth	800 mm
Supported storage drive interfaces	SAS, Serial ATA	Height	87 mm
Graphics		Weight	19 kg
On-board graphics card	✓	Technical details	
On-board graphics card model	Not available	Internal I/O Expansion Module x8 Gen 3	3
Maximum graphics card memory	16 MB	Number of 3.5" bays	8
Network		Sustainability certificates	ENERGY STAR
Ethernet LAN	✓	Other features	
Cabling technology	10/100/1000Base-T(X)	Graphics card	G200eR2
Ethernet interface type	Gigabit Ethernet	Graphics card family	Matrox
Ports & interfaces		Integrated BMC with IPMI	✓
Ethernet LAN (RJ-45) ports *	4	Integrated LAN	✓
USB 2.0 ports quantity	3		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-JAN-2024. Prints or copies of Information are only valid on the printed Publication date