

Brother ADS-1500W scanner ADF scanner 600 x 600 DPI Black, White

Brand : Brother Product code: ADS-1500W

Product name: ADS-1500W

ADS-1500W - Dual CIS, 18ppm, Duplex, 802.11 b/g/n, USB 2.0, 2.7" LCD, 1588g
Brother ADS-1500W. Maximum scan size: 215.9 x 863.6 mm, Optical scanning resolution: 600 x 600 DPI, Enhanced scan resolution: 1200 x 1200 DPI. Scanner type: ADF scanner, Product colour: Black, White, Display: LCD. Sensor type: Dual CIS, Daily duty cycle (max): 500 pages, Scan to: E-mail, E-mail Server, File, FTP, Image, OCR, USB. Auto document feeder (ADF) input capacity: 20 sheets. Scanning media types supported: Business Card, Photo paper, Plain paper, Plastic Card, Maximum scan area (ADF): 215.9 x 863.6 mm, Minimum scan area (ADF): 50.8 x 70.1 mm







Scanning		Power	
Optical scanning resolution * 600		Power supply type * Power consumption (typical) Power consumption (standby) Power consumption (PowerSave) Input voltage	AC 14 W 4 W 1.5 W 110-220 V
Input colour depth	24 bit	Network	
Output colour depth Film scanning Greyscale levels ADF scan speed (b/w, A4) ADF scan speed (colour, A4) Duplex ADF scan speed (b/w, A4) Duplex ADF scan speed (colour, A4) Black/white scanning colour modes	·	Wi-Fi Wi-Fi standards Mobile printing technologies Supported network protocols	802.11b, 802.11g, Wi-Fi 4 (802.11n) Brother iPrint & Scan ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS Resolver, mDNS, LLMNR, Custom Raw Port/Port9100, FTP Client/Server, SNMPv1/v2c, HTTP/HTTPS, TFTP Client/Server,
Design			ICMP, SNTP Client
Scanner type * Product colour * Display Display diagonal Touchscreen	ADF scanner Black, White LCD 6.86 cm (2.7") ✓	Packaging data Package width Package depth Package height Package weight	381 mm 170.1 mm 205.7 mm 2.59 kg
Performance			
Sensor type * Daily duty cycle (max) * Scan to Scan drivers	Dual CIS 500 pages E-mail, E-mail Server, File, FTP, Image, OCR, USB SANE, ICA, ISIS, TWAIN, WIA		
Input capacity			
Auto document feeder (ADF) input capacity	20 sheets		
Paper handling			
Scanning media types supported Maximum scan area (ADF)	Business Card, Photo paper, Plain paper, Plastic Card 215.9 x 863.6 mm		

Paper handling		System requirements	
Minimum scan area (ADF) Ports & interfaces	50.8 x 70.1 mm	Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
USB port * USB version Standard interfaces	2.0 USB 1.1, USB 2.0, Wireless LAN		
		Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion
		Linux operating systems supported	✓
		Operational conditions	
		Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	5 - 35 °C 15 - 85%
		Operating temperature (T-T) Operating relative humidity (H-H)	5 - 35 °C
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	5 - 35 °C 15 - 85%
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width	5 - 35 °C 15 - 85% 284.4 mm
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth	5 - 35 °C 15 - 85%
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width	5 - 35 °C 15 - 85% 284.4 mm 104.1 mm
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight	5 - 35 °C 15 - 85% 284.4 mm 104.1 mm 83.8 mm
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height	5 - 35 °C 15 - 85% 284.4 mm 104.1 mm 83.8 mm
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging content	5 - 35 °C 15 - 85% 284.4 mm 104.1 mm 83.8 mm 1.59 kg Nuance PDF Converter Professional 8 Nuance PaperPort 12SE Presto! PageManager 9 Presto! BizCard 6 Control Center 4 Control Center 2
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging content Bundled software	5 - 35 °C 15 - 85% 284.4 mm 104.1 mm 83.8 mm 1.59 kg Nuance PDF Converter Professional 8 Nuance PaperPort 12SE Presto! PageManager 9 Presto! BizCard 6 Control Center 4 Control Center 2
		Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging content Bundled software Other features	5 - 35 °C 15 - 85% 284.4 mm 104.1 mm 83.8 mm 1.59 kg Nuance PDF Converter Professional 8 Nuance PaperPort 12SE Presto! PageManager 9 Presto! BizCard 6 Control Center 4 Control Center 2 BR-Receipts Box, Dropbox, Evernote, Facebook, Flickr, Google Drive, Picasa, Sky

