

Epson C11CF37202 dot matrix printer 680 cps

Brand : Epson

Product code: C11CF37202

Product name : C11CF37202

9-pin, serial impact dot matrix, 680 cps (12 cpi), 55 dB, 414x350x167 mm

Epson C11CF37202 dot matrix printer 680 cps:

The Epson FX-890II Series offers the durability and ease of use for critical daily print requirements. These reliable 9-pin, narrow-carriage impact printers boast a long life cycle, a 3-year limited warranty and speeds up to 738 cps. Their up-to-7.5-million-character ribbon cartridge reduces user interventions as well as cost per page. Engineered for seamless integration into virtually any system, they include Epson ESC/P, IBM PPDS and MICROLINE printer languages. Ideal for harsh environments, these workhorses race through cut-sheet, continuous or multipart forms up to 7 pages thick, and feature an intuitive control panel for easy setup and operation.



Printing		Features	
Colour *	✗	Certification	RoHS
Maximum print speed *	680 cps	Ports & interfaces	
Maximum print speed (draft)	419 cps	Standard interfaces *	Parallel, USB, USB 1.1
Maximum print speed (LQ)	104 cps	Endurance	
Character pitch	10,12 cpi	Print head life	400 million characters
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, Matrix 2/5, POSTNET, UPC-A, UPC-E	Ribbon life	7.5 million characters
Bitmap fonts	Roman, Sans Serif	Mean time between failures (MTBF)	20000 h
Paper handling		Power	
Paper feed	Manual, Pull tractor, Push tractor	AC input voltage	103.5 - 132 V
Paper tray media types	Envelopes, Labels	AC input frequency	49.5 - 60.5 Hz
Cut sheet width range	99 - 256 mm	System requirements	
Cut sheet length range	99 - 363 mm	Windows operating systems supported	Windows 2000, Windows 95, Windows 98, Windows ME, Windows NT, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Continuous paper width range	10 - 254 mm	Weight & dimensions	
Continuous paper length range	101 - 558 mm	Width	414 mm
Features		Depth	350 mm
Product colour *	Black	Height	167 mm
Buffer size *	128 KB	Weight	7.62 kg
Sound pressure level (printing) *	55 dB	Technical details	
Page description languages *	ESC P, PPDS	Sustainability certificates	ENERGY STAR

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date