

Epson TM-T88V 180 x 180 DPI Wired & Wireless Thermal POS printer



Brand : Epson

Product code: C31CA85090

Product name : TM-T88V

- mPOS-friendly printer compatible with iOS, Android and Windows mobile devices
- DHCP enabled model available for easy IP/network configuration
- Printer class model available for easy connection and discovery
- Supports 802.11a/b/g/n with 2.4GHz/5GHz compatibility and Bluetooth® 2.1 + EDR
- Easy to configure and install
- Fast printing up to 300mm/sec for both text and graphics
- Special print options reduce paper usage up to 30%

TM-T88V-950 USB Powered EDG Printer, thermal, 300mm/sec, Dark Grey, w/o PS

Epson TM-T88V 180 x 180 DPI Wired & Wireless Thermal POS printer:

Fast, Reliable, Easy To Configure and Supports All The Leading Mobile Operating Systems Including IOS, Android and Windows

Epson's mPOS-friendly TM-T88V is the industry's leading POS thermal printer. It is fast, reliable, easy to configure and supports all the leading mobile operating systems including iOS, Android and Windows. It features fast printing up to 300mm/second, best-in-class reliability, multiple ease-of-use features, dual interfaces and print options that reduce paper usage up to 30%.

Printing		Power	
Maximum resolution	180 x 180 DPI	Power source type *	USB
Print speed	300 mm/sec	Operational conditions	
Print technology *	Thermal	Operating temperature (T-T)	5 - 45 °C
Type *	POS printer	Storage temperature (T-T)	-10 - 50 °C
Paper handling		Operating relative humidity (H-H)	10 - 90%
Printing media thickness	55 - 80 µm	Storage relative humidity (H-H)	10 - 90%
Maximum roll diameter	8.3 cm	System requirements	
Supported paper width	80, 58 mm	Windows operating systems supported	✓
Maximum printing width	7.2 cm	Mac compatibility	✓
Ports & interfaces		Mac operating systems supported	✓
USB port *	✓	Mobile operating systems supported	Android, Windows Mobile, iOS
Connectivity technology *	Wired & Wireless	Linux operating systems supported	✓
Features		Weight & dimensions	
Built-in barcodes *	CODABAR (NW-7), GS1 DataBar, GS1-128, MaxiCode, PDF417, QR Code	Width	145 mm
Mean time between failures (MTBF)	360000 h	Depth	195 mm
Cutter	✓	Height	148 mm
Autocutter durability	2 million cuts	Weight	1.6 kg
Certification	FCC/ICES-003 Class A UL1950/CSA C22.2 No. 950		
Design			
Product colour *	Grey		
Built-in display	✗		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date