

Epson TM-T70II Wired & Wireless Thermal POS printer

Brand : Epson

Product code: C31CD38A9991

Product name : TM-T70II



250mm/s, USB, Bluetooth 2.1+EDR, 802.11b/g/n, Black

Epson TM-T70II Wired & Wireless Thermal POS printer:

Epson's mPOS-friendly TM-T70II POS printer, with its small size and low height (only 4.49" high), is designed to fit under a counter, in kiosks and other small spaces. It features fast printing of up to 250mm/second, industry-leading reliability, dual interfaces and more. And it supports all the leading mobile operating systems including iOS, Android and Windows.



- mPOS-friendly printer compatible with iOS, Android and Windows mobile devices
- DHCP enabled model available for easy IP/network configuration
- Printer class model available for easy connection and discovery
- Supports 802.11a/b/g/n with 2.4GHz/5GHz and Bluetooth® 2.1 + EDR
- Designed to fit under counters
- Front-facing controls, paper loading and receipt dispensing
- Fast printing up to 250mm/sec
- Paper saving options reduce usage up to 30%
- Enables intelligent couponing triggered by keywords/sequence
- Two-year limited warranty

Printing		Features	
Print speed	250 mm/sec	Safety	UL/CSA/EN/TUV/GOST-R
Character size	2.82 x 6.77 mm	Certification	RoHS, WEEE
Character density	20 cpi	Design	
Print technology *	Thermal	Product colour *	Black
Type *	POS printer	Power	
Paper handling		AC input voltage	100-240 V
Supported paper width	80 mm	AC input frequency	50 - 60 Hz
Ports & interfaces		Power consumption	2000 mA
USB port *	✓	Weight & dimensions	
Bluetooth	✓	Width	125 mm
Bluetooth version	2.1+EDR	Depth	194 mm
Connectivity technology *	Wired & Wireless	Height	114 mm
Standard interfaces	Bluetooth, USB	Weight	1.7 kg
Network		Packaging data	
Ethernet LAN *	✗	Cables included	AC, USB
Wi-Fi *	✓	Packaging content	
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Drivers included	✓
Features		Quick start guide	✓
Built-in barcodes *	CODABAR (NW-7), Code 39, Code 93, Code-128 Codabar Library, EAN13, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E	Print technology	
Mean time between failures (MTBF)	360000 h	Column capacity	42/56
Autocutter durability	1.7 million cuts	Other features	
		LED indicators	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date