

Epson OmniLink TM-m30II-NT 203 x 203 DPI Wired Thermal POS printer



Brand : Epson

Product code: C31CJ95022

Product name : OmniLink TM-m30II-NT

Thermal, 250 mm/sec, 203 x 203 DPI, USB, Ethernet, 127 x 127 x 135 mm, 1.3 kg

[Epson OmniLink TM-m30II-NT 203 x 203 DPI Wired Thermal POS printer:](#)

The OmniLink TM-m30II-NT POS thermal receipt printer includes both USB and Ethernet connectivity. A compact 3" receipt printer with a modern, industrial design, it can charge a tablet or smartphone, and communicate data using a single USB cable¹ (cable not included). The TM-m30II-NT also offers USB-Network-Tethering, which enables network connection to a tablet, making it perfect for locations that experience issues with wireless connectivity. Built to support a USB POS peripheral device, it enables online ordering through Server Direct Print and supports cloud applications through OmniLink Merchant Services. The TM-m30II-NT speeds through prints at up to 250 mm/sec.

Printing		Features	
Maximum resolution	203 x 203 DPI	Mounting position	Horizontal/Vertical
Print speed	250 mm/sec	Wall mountable	✓
Printing characters	Barcode, Graphic, Text	Design	
Character sets	ANK	Product colour *	Black
Print technology *	Thermal	Power	
Type *	POS printer	Power source type *	AC
Paper handling		Operational conditions	
Printing media thickness	48 - 80 µm	Operating temperature (T-T)	5 - 45 °C
Maximum roll diameter	8.3 cm	Storage temperature (T-T)	-20 - 60 °C
Supported paper width	58 - 80 mm	Operating relative humidity (H-H)	10 - 90%
Maximum printing width	7.95 cm	Storage relative humidity (H-H)	10 - 90%
Roll core diameter (max)	1.8 cm	System requirements	
Ports & interfaces		Windows operating systems supported	✓
USB port *	✓	Mac compatibility	✓
USB 2.0 ports quantity	3	Mobile operating systems supported	Android, iOS
USB connector	USB Type-A / USB Type-B	Linux operating systems supported	✓
Serial interface *	✗	Weight & dimensions	
Connectivity technology *	Wired	Width	127 mm
Network		Depth	127 mm
Ethernet LAN *	✓	Height	135 mm
Features		Weight	1.3 kg
Built-in barcodes *	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E		
Cutter	✓		
Autocutter durability	2.2 million cuts		
Print head life	150 km		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2024. Prints or copies of Information are only valid on the printed Publication date