



HP LaserJet Color CM4730fm Laser A4 30 ppm

Brand : HP

Product family: LaserJet

Product code: CB483A

Product name : Color LaserJet CM4730fm



Color LaserJet CM4730f MFP 30 ppm A4, 600 x 600 dpi, Fax 33.6 Kbps, Scan Flatbed, ADF, Duplex print, Fast Ethernet

HP LaserJet Color CM4730fm Laser A4 30 ppm:

The perfect tool for mid-volume workgroups of 6 to 15 users in both small and medium businesses and enterprise environments, this fast, colour MFP enables them to be more productive with print, copy, send-to functionality, fax (optional), plus HP and key partner solutions close at hand.

HP LaserJet Color CM4730fm. Print technology: Laser, Printing: Colour printing, Print speed (colour, normal quality, A4/US Letter): 30, 31. Copying: Colour copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A4



| Printing | | Power | |
|---|-----------------|---|--|
| Print technology * | Laser | Power consumption (average operating) | 640 W |
| Printing * | Colour printing | Power consumption (PowerSave) | 25 W |
| Duplex printing * | ✓ | Power consumption (off) | 0.5 W |
| Print speed (black, normal quality, A4/US Letter) * | 30 ppm | Operational conditions | |
| Print speed (colour, normal quality, A4/US Letter) | 30, 31 | Operating relative humidity (H-H) | 10 - 80% |
| Print speed (black, draft quality, A4/US Letter) | 30, 31 | Recommended operating temperature range (T-T) | 17 - 25 °C |
| Print speed (colour, draft quality, A4/US Letter) | 30 ppm | Storage temperature (T-T) | -20 - 40 °C |
| Warm-up time | 165 s | Operating temperature (T-T) | 15 - 30 °C |
| Time to first page (black, normal) | 11 s | Storage relative humidity (H-H) | 10 - 90% |
| Time to first page (colour, normal) | 11 s | Operating temperature (T-T) | 62.6 - 77 °F |
| Print speed (black, best quality, A4) | 30 ppm | Operating altitude (imperial) | 8530 ft |
| Print speed (colour, best quality, A4) | 30 ppm | Sustainability | |
| Print speed (black, best quality, letter) | < 31 ppm | Sustainability certificates | Blue Angel, ENERGY STAR |
| Print speed (colour, best quality, letter) | < 31 ppm | Weight & dimensions | |
| Print speed (colour, draft quality, letter) | < 31 ppm | Weight | 136 kg |
| Copying | | Packaging data | |
| Copying * | Colour copying | Package weight | 169.4 kg |
| Maximum copy resolution * | 600 x 600 DPI | Packaging content | |
| | | Bundled software | Windows Installer for 2k and up x86 and x64; Mac Installer for OS 10.2 and up; |

| Copying | | Logistics data | |
|---|---|---|--|
| Copy speed (black, normal quality, A4) | 30 cpm | Pallet gross weight | 169.4 kg |
| Copy speed (colour, normal quality, A4) | 30 cpm | Products per pallet | 1 pc(s) |
| Time to first copy (letter) | Less than 10 sec | Other features | |
| Maximum number of copies | 999 copies | Standard input trays | 4 |
| Copy resolution (black graphics) | Up to 600 x 600 dpi | I/O ports | Bidirectional IEEE-1284-C parallel port, Hi-Speed USB 2.0 port, one open EIO slot, foreign interface harness, accessory port |
| Copy resolution (colour text and graphics) | 600 DPI | Networking features | Fast Ethernet |
| Left metric copy margin | 4.2 | Dimensions (WxDxH) | 1106 x 639 x 1153 mm |
| Right metric copy margin | 4.2 | Acoustic power emissions | 6.7 B(A) |
| Top metric copy margin | 4.2 | Acoustic pressure emissions | 50 dB |
| Copier settings | Scalability, contrast, background removal, sharpness, N- or Z-ordering, orientation | Copier smart software features | Scalability, contrast, background removal, sharpness, N- or Z-ordering, orientation |
| Bottom copy margin | 4.2 | Custom media sizes | Multipurpose tray: 76 x 127 to 216 x 356 mm, Trays 2, 3, 4: 148 x 210 to 216 x 356 mm, custom sizes not supported on automatic two-sided printing, optional 3-bin mailbox or stapler part of the optional stapler/stacker Multipurpose tray: 3 x 5 to 8.5 x 14 in, Trays 2, 3, 4: 5.83 x 8.27 to 8.5 x 14 in, custom sizes not supported on automatic two-sided printing, optional 3-bin mailbox or stapler part of the optional stapler/stacker |
| Maximum copy speed (black, A4) | 30 cpm | Duplex print options | Automatic (standard) |
| Maximum copy speed (colour, A4) | 30 cpm | Duty cycle letter size (maximum) | 175000 pages per month |
| Copy speed (black, best, letter) | 31 cpm | Media weights by paper path | Multipurpose tray: 60 to 220 g/m ² , Trays 2, 3, 4: 60 to 120 g/m ² , automatic two-sided printing, optional 3-bin mailbox, stapler part of the optional stapler/stacker: 60 to 120 g/m ² |
| Scanning | | Network ready | ✓ |
| Scanning * | Colour scanning | Pallet dimensions (W x D x H) | 900 x 815 x 1636 mm |
| Optical scanning resolution * | 600 x 600 DPI | Power requirements | 100 - 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220 - 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) |
| Scanner type * | Flatbed scanner | Print quality (black, draft quality) | 600 DPI |
| Input colour depth | 30 bit | Print quality (colour, best quality) | 600 DPI |
| Greyscale levels | 256 | Printer management | HP Web Jetadmin; HP Easy Printer Care (Neither is shipped in box) |
| Scan input modes | Copy, E-mail, Fax, Secondary e-mail, Folder, Workflow | Standard media sizes | C5, DL, Dpostcard (JIS), 16k |
| Scan speed (black, normal quality) | 30 ipm | Typefaces | 80 internal TrueType fonts scalable in HP PCL and HP Postscript Level 3 emulation; additional font solutions available via Flash memory |
| Scan speed (colour, normal quality) | 30 ipm | Modem type | 33.6 kbps Up to 33.6 kbps - internal modem for JBIG compression and NOT APPLICABLE for other compressions depends on the vendor's modem firmware. Not hot swappable, PC Fax Software optional, Support for LAN fax 3rd party software, DSS supports LAN fax . |
| Minimum scan size | 14.8 x 12.7 cm | Media types supported | Paper (plain, preprinted, letterhead, prepunched, bond, recycled, color, light, intermediate, heavy, extra heavy, rough, glossy, heavy glossy, tough), transparencies, labels, envelopes, card stock Legal, letter, A4, A5 |
| Fax | | Minimum system requirements for Macintosh | Mac OS X v10.2.8, 10.3, 10.4, 10.5, 10.6, 128 MB RAM, 25 MB available hard disk space; network or USB port |
| Faxing * | Colour faxing | Print quality (black, best quality) | 600 x 600 DPI |
| Modem speed | 33.6 Kbit/s | | |
| Auto-redialing | ✓ | | |
| Fax speed dialing (max numbers) | 100 | | |
| Fax forwarding | ✓ | | |
| Fax broadcasting | 100 locations | | |
| Fax delayed sending | ✗ | | |
| Distinctive ring | ✗ | | |
| Features | | | |
| Maximum duty cycle * | 175000 pages per month | | |
| Digital sender | ✗ | | |
| Number of print cartridges * | 4 | | |
| Printing colours * | Cyan, Magenta, Yellow | | |
| All-In-One-multitasking | ✓ | | |
| Input & output capacity | | | |
| Total input capacity * | 1600 sheets | | |
| Total output capacity * | 500 sheets | | |
| Auto document feeder (ADF) | ✓ | | |
| Auto document feeder (ADF) input capacity | 50 sheets | | |
| Input capacity for envelopes (primary tray) | 20 sheets | | |
| Maximum input capacity for envelopes | Up to 20 envelopes | | |
| Standard output capacity for envelopes | 20 sheets | | |
| Maximum input capacity | 1600 sheets | | |
| Maximum output capacity | 700 sheets | | |
| Paper handling | | | |
| Maximum ISO A-series paper size * | A4 | | |

| Other features | |
|---|--|
| Acoustic pressure emissions bystander (ready) | Inaudible |
| Auto fax reduction supported | ✓ |
| Copier scaling (Auto Document Feeder) | 25 - 200% |
| Duplex binding | ✓ |
| First page out (black&white, A4, ready) | 13 s |
| First page out (black&white, letter, ready) | 12 s |
| First page out (black&white, letter, sleep) | 17.5 s |
| Handset | ✗ |
| Junk barrier supported | ✓ |
| Maximum scan area (ADF) (imperial) | 215.9 x 355.6 mm (8.5 x 14") |
| Media sizes supported (imperial) | Letter, legal, executive, statement, 8.5 x 13 in, envelopes (No. 10, commercial) |
| Minimum scan area (Auto Document Feeder) | 215.9 x 355.6 mm (8.5 x 14") |
| Minimum scan area | 147.3 x 127 mm (5.8 x 5") |
| Multi feed detection | ✗ |
| Package weight (imperial) | 372.7 s |
| Product dimensions optional (metric) | 1106 x 639 x 1153 mm |
| SureSupply connection type | Direct and Network |
| SureSupply supported | ✓ |
| Wireless option type | Optional, enabled with purchase of a hardware accessory |
| UNSPSC-code | 43212105 |
| Security management description | Management security: password protection, SNMP v3, SSL/TLS (HTTPS), 802.1x authentication (EAP- PEAP, EAP-TLS), central and remote security configuration through WJA, EPC, and Jetdirect Security Configuration Wizard |
| All-in-one functions | Copy, Fax, Scan |
| Colour all-in-one functions | Copy, Fax, Print, Scan |
| Package dimensions (WxDxH) | 900 x 815 x 1636 mm |
| Media size (tray 1) | A4, A5, B5 (JIS), executive (JIS), 16K, D Postcard (JIS), envelopes (DL, C5, B5), custom 76 x 127 to 216 x 356 mm |
| Electromagnetic compatibility | CISPR 22:2005 / EN 55022:2006 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995, EN 55024:1998, FCC Title 47 CFR, Part 15 Class A / ICES-003, Issue 4 / GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC and carries the CE-Marking accordingly |



0882780900462



882780900462



8291609728248



0882780900455



882780900455



0882780900387



882780900387



0882780900370



882780900370



0882780900424



882780900424



0882780900486



882780900486




0882780900363



882780900363



0882780900554



882780900554



0882780900547



882780900547



0882780900530



882780900530




0882780900523



882780900523



0882780900516



882780900516




0882780900509



882780900509



0882780900493



882780900493



0882780900479



882780900479



0882780900448



882780900448



0882780900431



882780900431



0882780900417



882780900417



0882780900400



882780900400



0882780900394



882780900394

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.