



# HP OfficeJet J4680 Thermal inkjet A4 4800 x 1200 DPI 9 ppm

Brand : HP

Product family: OfficeJet

Product code: CB783A

Product name : J4680

Officejet J4680 All-in-One Printer, Inkjet, 9ppm, A4, 120MHz, 32MB, LCD

HP OfficeJet J4680 Thermal inkjet A4 4800 x 1200 DPI 9 ppm:

**Low cost per page, built-in 802.11g wireless networking, print/copy at up to 28 ppm black, 22 ppm colour, 4-ink colour, HP Officejets inks, optional XL black cartridge, up to 4800-optimised dpi, dual drop weight technology, 20-sheet Automatic Document Feeder, 33.6 Kbps modem, 100-page fax memory, 99-number speed dial memory, copy without a PC, scan-to-email, scan-to-network folder or PC, 1200 x 2400 dpi scan resolution, 100-sheet paper tray, text display, ink backup mode, HP Smart Web Printing, HP Solution Center software**

Streamline the way you work - print, fax, scan and copy from this easy-to-use wireless all-in-one<sup>[2]</sup>. Enjoy the speed and convenience of a 20-page ADF. Print high-quality colour documents for up to 15% less cpp than colour lasers<sup>[1]</sup>.



Printing		Network	
Print technology *	Thermal inkjet	Wi-Fi *	✗
Printing *	Mono printing	Ethernet LAN *	✗
Duplex printing *	✗	Performance	
Maximum resolution *	4800 x 1200 DPI	Maximum internal memory	32 MB
Print speed (black, normal quality, A4/US Letter) *	9 ppm	Card reader integrated	✗
Print speed (colour, normal quality, A4/US Letter)	6.5 ppm	Internal memory *	32 MB
Print speed (black, draft quality, A4/US Letter)	28 ppm	Processor frequency	120 MHz
Print speed (colour, draft quality, A4/US Letter)	22 ppm	Sound pressure level (printing)	56 dB
Print speed (black, best quality, A4)	2.5 ppm	Design	
Print speed (colour, best quality, A4)	2.5 ppm	Product colour *	Black, White
Print speed (black, best quality, letter)	< 2.5 ppm	Market positioning *	Home & office
Print speed (colour, best quality, letter)	< 2.5 ppm	Built-in display *	✓
Print speed (colour, draft quality, letter)	< 22 ppm	Display	LCD
Copying		Power	
Duplex copying *	✗	Power consumption (average operating)	9.6 W
Copying *	Colour copying	Power consumption (off)	0.4 W
Maximum copy resolution *	4800 x 1200 DPI	AC input frequency	50 - 60 Hz
Copy speed (black, normal quality, A4)	28 cpm	System requirements	
Copy speed (colour, normal quality, A4)	5.5 cpm	Windows operating systems supported	Windows 2000, Windows 7, Windows Vista, Windows XP
Copy speed (colour, normal, US Letter)	7.6 cpm	Mac operating systems supported	Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard
Maximum number of copies	90 copies	Linux operating systems supported	✓
Copier resize	25 - 400%	Server operating systems supported	Windows Server 2008
Copy resolution (black graphics)	Up to 600 x 1200 dpi Optimized on select HP photo papers with 600 scan dpi	Operational conditions	
Copier settings	Stand-alone copying: Actual size, Fit to page, Custom, Full page, Legal to letter	Operating relative humidity (H-H)	15 - 85%
Maximum copy speed (black, A4)	28 cpm	Recommended operating temperature range (T-T)	15 - 32 °C
		Storage temperature (T-T)	-40 - 60 °C
		Operating temperature (T-T)	5 - 40 °C
		Operating temperature (T-T)	59 - 90 °F

<b>Copying</b>		<b>Sustainability</b>	
Maximum copy speed (colour, A4)	22 cpm	Sustainability certificates	ENERGY STAR
Copy speed (black, best, letter)	Up to 0.8 cpm	<b>Weight &amp; dimensions</b>	
<b>Scanning</b>		Width	434 mm
Duplex scanning *	✗	Depth	402 mm
Scanning *	Colour scanning	Height	217 mm
Optical scanning resolution *	1200 x 1200 DPI	Weight	5.9 kg
Maximum scan area	216 x 297 mm	<b>Packaging data</b>	
Scanner type *	Flatbed scanner	Package width	475 mm
Scan technology	CIS	Package depth	250 mm
Input colour depth	48 bit	Package height	345 mm
Greyscale levels	256	Package weight	7.64 kg
TWAIN version	Version 10.0	<b>Logistics data</b>	
Scan input modes	Front Panel, HP photo and imaging software, TWAIN compliant program, WIA compliant program	Pallet gross weight	590 kg
<b>Fax</b>		Master (outer) cases per pallet	10 pc(s)
Duplex faxing	✗	Layers per pallet	7 pc(s)
Faxing *	Colour faxing	Products per pallet	70 pc(s)
Fax resolution (black)	300 x 300 DPI	<b>Other features</b>	
Fax transmission speed	3 sec/page	Standard input trays	1
Fax memory	100 pages	I/O ports	1 USB, 1 Phone, 1 Ext Phone
Auto-redialing	✓	Dimensions (WxDxH)	434 x 402 x 217 mm
Fax speed dialing (max numbers)	99	Acoustic power emissions	7.0 B(A)
Fax forwarding	✓	Compatible ink types, supplies	Dye-based (colour), pigment-based (black)
Fax broadcasting	48 locations	Custom media sizes	77 x 127 to 216 x 356 mm
Fax delayed sending	✓	Duplex print options	None (not supported)
Distinctive ring	✓	Network ready	✓
<b>Features</b>		Pallet dimensions (W x D x H)	1219.2 x 1016 x 2542 mm
Maximum duty cycle *	3000 pages per month		A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), C6 (114 x 162 mm), DL (99 x 210 mm) 130 x 180 mm, 100 x 150 mm (with or without tear-off/cut-off tab)
Digital sender	✗	Standard media sizes	
Number of print cartridges *	2	Typefaces	✗
Printing colours *	Black, Cyan, Magenta, Yellow	Modem type	33.6 Kbps
All-In-One-multitasking	✓	Print quality (black, best quality)	600 x 600 DPI
<b>Input &amp; output capacity</b>		Standard output capacity for transparencies	10 sheets
Total input capacity *	120 sheets	Image scaling/enlargement range	25 - 400%
Total output capacity *	20 sheets	Compatible operating systems	Windows 2000, XP Home, XP Professional, XP Professional x64; Windows Vista, x64; Mac OS X v10.3.9, v10.4.x, v10.5.
Auto document feeder (ADF)	✓	Automatic paper sensor	✗
Auto document feeder (ADF) input capacity	20 sheets	Maximum scan area (imperial)	21.6 cm (8.5")
Maximum input capacity for envelopes	Up to 15	Package dimensions (W x D x H)	475 x 249.9 x 344.9 mm (18.7 x 9.84 x 13.6")
Maximum input capacity for labels	Up to 20 sheets	Pallet dimensions (W x D x H) (imperial)	1219.2 x 1016 x 2542.5 mm (48 x 40 x 100.1")
Maximum input capacity for transparencies	25 sheets	Pallet weight (imperial)	589.7 kg (1300 lbs)
Maximum input capacity for 10 x 15 cm photographs	40 sheets	Size (imperial)	43.4 cm (17.1")
Standard output capacity for cards	Up to 10 cards	Auto fax reduction supported	✓
Maximum input capacity	100 sheets	Junk barrier supported	Yes (requires Caller ID)
Maximum output capacity	20 sheets	Maximum scan area (ADF) (imperial)	215.9 x 355.6 mm (8.5 x 14")
<b>Paper handling</b>		Media sizes supported (imperial)	Letter, legal, executive, cards
Maximum ISO A-series paper size *	A4	Package weight (imperial)	8.13 kg (17.9 lbs)
Maximum print size	210 x 297 mm	Recommended media weight (imperial)	16 to 24 lb
Paper tray media types *	Card stock, Envelopes, Iron-On Transfers, Labels, Photo paper, Plain paper	Send to email capability	✗
ISO A-series sizes (A0...A9) *	A4, A5	Standard input capacity for legal	100 sheets
ISO B-series sizes (B0...B9)	B5	Standard output capacity for labels	10 sheets
Envelopes sizes	C6, DL	Standard output capacity for legal	25 sheets
Envelope feeder	✗		
Recommended media weight	70 - 90 g/m <sup>2</sup>		

Paper handling		Other features	
Maximum input capacity for cards	40	SureSupply supported	✓
Media handling	Sheetfed	Vivera inks supported	✗
Maximum paper trays	1	Wireless option type	Yes, with built-in wireless 802.11 b/g
Paper handling optional/input	None	Case or master carton quantity	28 pc(s)
Paper handling standard/input	100-sheet input tray, 20-sheet Automatic Document Feeder (ADF)	UNSPSC-code	43212110
Paper handling standard/output	20-sheet output tray	All-in-one functions	Copy, Fax, Print, Scan
Ports & interfaces		Colour all-in-one functions	Copy, Fax, Scan
Standard interfaces	USB 2.0	Package dimensions (WxDxH)	475 x 250 x 345 mm
Direct printing *	✗	Media size (tray 1)	A4, B4, B5, C7, 175 x 440 to 150 x 150 mm
USB port	✓		



0883585978335




883585978335




0883585978366



883585978366



0883585978328



883585978328



0883585786008



883585786008



0884420690610



884420690610



0883585978342



883585978342



0883585978311




883585978311



0883585978304



883585978304



0883585978359



883585978359



0883585978373



883585978373



0883585978380



883585978380

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.