



## HP LaserJet Color CP1515n Printer Colour 600 x 600 DPI A4



Brand : HP

Product family: LaserJet

Product code: CC377A

Product name : Color LaserJet CP1515n Printer

Color LaserJet CP1515n 8 ppm 600 x 600dpi /12 ppm black, HP ImageREt 3600

HP LaserJet Color CP1515n Printer Colour 600 x 600 DPI A4:

Create high-impact business communications in-house, easily and affordably with this fast, reliable HP Color LaserJet. Get vibrant colour, high gloss and photo-quality images with new formula HP ColorSphere toner. HP ImageREt 3600 enables your printer to produce high quality images, text and graphics on a wide range of different media. Print at speeds of up to 12 ppm black and 8 ppm colour. Enjoy ease of use with a new, intuitive driver interface and basic-featured networking for up to 5 users.

HP LaserJet Color CP1515n Printer. Print technology: Laser, Colour. Number of print cartridges: 4. Maximum resolution: 600 x 600 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 12 ppm. Display: LCD. Network ready

Printing		Other features	
Print speed (colour, normal quality, A4/US Letter)	8 ppm	Media weights by paper path	Tray 1, 2: 60 to 176 g/m <sup>2</sup> (up to 200 g/m <sup>2</sup> with HP laser cover papers, up to 220 g/m <sup>2</sup> with HP laser glossy photo papers)
Colour *	✓	Recommended media weight	60 - 176 g/m <sup>2</sup>
Print technology *	Laser	Standard output capacity for envelopes	10 sheets
Duplex printing *	✗	Minimum system requirements	Microsoft Windows 2000, XP Home, XP Professional, Server 2003, Windows Vista (32 and 64 Bit): 512 MB RAM, 350 MB hard disk space, CD-ROM drive, available USB port
Maximum resolution *	600 x 600 DPI	Envelope feeder	✗
Print speed (black, normal quality, A4/US Letter) *	12 ppm	Printer management	Toolbox, HP Web JetAdmin, embedded Web server
Time to first page (black, normal)	25.5 s	Acoustic power emissions	6.2 B(A) (printing at 12 ppm), 3.1 B (A) (ready)
Features		Power requirements	Input voltage 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz)
Number of print cartridges *	4	Print quality (colour, best quality)	600 DPI
Input & output capacity		Duplex print options	Manual (driver support provided)
Total input capacity *	150 sheets	Duty cycle letter size (maximum)	30000 pages per month
Total output capacity *	125 sheets	Print speed (colour, best quality, A4)	8 ppm
Maximum output capacity	125 sheets	Print speed (black, best quality, A4)	12 ppm
Paper handling		Paper handling	Single-sheet priority feed slot, 150-sheet input tray, 125-sheet face-down output bin
Maximum ISO A-series paper size *	A4	Electromagnetic compatibility	CISPR 22: 2005/EN 55022: 2006 Class B, EN 61000-3-2: 2000+A2, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries
Paper tray media types *	Bond paper, Envelopes, Glossy paper, Labels, Plain paper, Recycled paper, Transparencies	Standard input trays	2
ISO A-series sizes (A0...A9) *	A4, A5, A6	Networking features	Via On-board internal networking, via HP Jetdirect external print servers 10/100Base-TX with RJ45 connector
JIS B-series sizes (B0...B9)	B5	Print quality (black, best quality)	600 x 600 DPI
Media types supported	Paper (bond, brochure, colour, glossy, letterhead, photo, plain, preprinted, prepunched, recycled, rough), transparencies, labels, envelopes, cardstock	Standard output capacity for transparencies	50 sheets
Media size (tray 1)	A4, A5, A6, B5 (ISO, JIS), 76 x 127 to 216 x 356 mm		
Media weight (tray 1)	60 to 176 g/m <sup>2</sup> (up to 200 g/m <sup>2</sup> with HP Laser Cover papers, up to 220 g/m <sup>2</sup> with HP Color Laser Glossy Photo papers)		
Network			
Network ready	✓		
Performance			
Internal memory *	96 MB		
Built-in processor	✓		
Processor model	Motorola Coldfire V5x		
Processor frequency	450 MHz		

Design		Other features	
Display	LCD	Driver updates	Latest drivers for Windows and Mac are available at <a href="http://support/ljcp1510series">http://support/ljcp1510series</a>
System requirements		Media handling	Sheetfed
Minimum system requirements for Macintosh	Mac OS X v10.2.8, v10.3.9, v10.4 and higher: 256 MB RAM, 150 MB available hard disk space, CD-ROM drive, USB port	Memory technology	Memory Enhancement technology (MET)
Operational conditions		Control panel	2-line, 16-character front panel display, 5 buttons (Cancel job, Left arrow, Right arrow, Select, Reverse), 2 LEDs (Attention, Ready)
Operating temperature (T-T)	15 - 32.5 °C	Maximum paper trays	2
Storage temperature (T-T)	-20 - 40 °C	Media size (tray 2)	A4, A5, A6, B5 (ISO, JIS), 76 x 127 to 216 x 356 mm
Operating relative humidity (H-H)	10 - 80%	Media type and capacity (tray 2)	sheets: 150, transparencies: 50, cards: 50, envelopes: 10
Storage relative humidity (H-H)	10 - 95%	Media weight (tray 2)	60 to 176 g/m <sup>2</sup> (up to 200 g/m <sup>2</sup> with HP Laser Cover papers, up to 220 g/m <sup>2</sup> with HP Color Laser Glossy Photo papers)
Operating temperature (T-T)	68 - 81 °F	Paper handling standard/input	Single-sheet priority feed slot, 150-sheet input tray, 125-sheet face-down output bin
Sustainability		Paper handling standard/output	125-sheet face-down output bin
Sustainability certificates	Blue Angel, ENERGY STAR	Safety	IEC 60950-1 (International), EN 60950-1+A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries
Weight & dimensions		Security management description	Password-protected network embedded Web server
Maximum dimensions (W x D x H)	399 x 453 x 254 mm	Downloadable software	Universal Print Driver for Windows, Windows CD image, Mac CD Image, Web JetAdmin, Easy Printer Care, Basic Color Match, Smart Web Printing In-House Marketing, Unix/Linux driver, Enterprise installer utility, Plug and Play bundles
Pallet dimensions (W x D x H)	1200 x 1000 x 2239 mm	Compatible operating systems	Microsoft Windows 2000, XP Home, XP Professional, Server 2003; Windows Vista Ready; Mac OS X v10.2.8, v 10.3, v10.4 or higher
Weight	18.2 kg	Package dimensions (W x D x H)	597.9 x 497.8 x 365.8 mm (23.5 x 19.6 x 14.4")
Dimensions (WxDxH)	399 x 453 x 254 mm	Pallet dimensions (W x D x H) (imperial)	1199.9 x 1000 x 2238.8 mm (47.2 x 39.4 x 88.1")
Packaging data		Pallet weight (imperial)	580.8 kg (1280.4 lbs)
Package weight	23.5 kg	Product dimensions when open (LxWxD)	39.9 cm (15.7")
Packaging content		Weight (imperial)	39.9 lb
Bundled software	Print drivers (HP PCL 6, HP Postscript level 3 emulation), Toolbox configuration utility	Acoustic pressure emissions bystander (active, print, copy or scan)	48.5 dB(A)
Logistics data		Duplex binding	✗
Pallet gross weight	582 kg	First page out (black&white, A4, ready)	25.5 s
Master (outer) cases per pallet	4 pc(s)	First page out (black&white, letter, ready)	25.5 s
Layers per pallet	6 pc(s)	Media sizes supported (imperial)	Letter, legal, executive, envelopes (No 10, Monarch)
Products per pallet	24 pc(s)	Operating altitude (imperial)	Up to 10,000 ft
Other features		Package weight (imperial)	23.5 kg (51.7 lbs)
Print quality (black, normal quality)	600 DPI	Print speed (black, best quality, letter)	< 12
Recommended operating temperature range (T-T)	20 - 27 °C	Print speed (colour, best quality, letter)	< 8
I/O ports	1 Hi-Speed USB (compatible with USB 2.0 specifications), 1 10/100Base-TX with RJ45 connector		
Input capacity for envelopes (primary tray)	10 sheets		
Custom media sizes	76 x 127 to 216 x 356 mm		
Standard media sizes	A4, A5, A6, B5 (ISO, JIS)		
Print margin bottom (A4)	3.5 mm		
Print margin left (A4)	3.5 mm		
Print margin right (A4)	3.5 mm		
Print margin top (A4)	3.5 mm		
Typefaces	80 scalable TrueType fonts		

### Other features

Size (imperial)	39.9 cm (15.7")
Acoustic power emissions (ready)	31 dB
Acoustic pressure emissions bystander (ready)	Inaudible
Automatic paper sensor	✘
SureSupply connection type	Direct and Network
SureSupply supported	✔
Typical electricity consumption (TEC) number	1.04 kWh/Week
Package dimensions (WxDxH)	598 x 498 x 367 mm



883585140503



0884420722335




884420722335



0883585140503




883585140503



0883585140435




883585140435




0883585140411



883585140411



5051395705303



0883585140473



883585140473



0883585140480




883585140480



0883585140497




883585140497



0883585140510




883585140510



0883585140527



883585140527



0883585140534




883585140534



0883585140541



883585140541



0883585140558




883585140558




0883585140565



883585140565




0883585528189



883585528189



0883585528202



883585528202



0883585528196



883585528196



0883585139910



883585139910



0883585139927




883585139927




0883585140312



883585140312



0883585140329



883585140329



0883585140336



883585140336



0883585140343



883585140343



0883585140350



883585140350



0883585140367




883585140367




0883585140374




883585140374



0883585140381




883585140381



0883585140398



883585140398



0883585140404




883585140404



0883585140428



883585140428



0883585140442




883585140442



0883585140459



883585140459



0883585140466



883585140466

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.