



# HP LaserJet Enterprise MFP M725z+ Laser A3 1200 x 1200 DPI 41 ppm

**Brand :** HP

**Product family:** LaserJet Enterprise

**Product code:** CF069A

**Product name :** HP LaserJet Enterprise MFP M725z+, Black and white, Printer for Business, Print, copy, scan, fax, 100-sheet ADF; Front-facing USB printing; Scan to email/PDF; Two-sided printing

HP LaserJet Enterprise Multifunction M725z+, Laser, 41ppm, A3, 800MHz, 1024MB, 20.3" LCD

HP LaserJet Enterprise MFP M725z+ Laser A3 1200 x 1200 DPI 41 ppm:

**As HP LaserJet Enterprise MFP M725dn, with built-in fax; 500-sheet inline stapler/stacker; 3500-sheet feeder and stand.**

Enable large-volume printing on a wide range of paper sizes – up to A3 – with a 4,600-sheet maximum input capacity.<sup>[1]</sup> Preview and edit scanning jobs; centrally manage printing policies; safeguard sensitive business information.

HP LaserJet Enterprise MFP M725z+. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Duplex functions: Print, Copy, Scan. Maximum ISO A-series paper size: A3. Direct printing. Product colour: Black, Grey



Printing		Network	
Duplex printing mode	Auto	Supported network protocols (IPv4)	AutoIP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print
Print resolution black	1200 x 1200 DPI	Supported network protocols (IPv6)	DHCPv6, MLDv1, ICMPv6
Print technology *	Laser	Security features	AES 256-bit
Printing *	Mono printing	Mobile printing technologies	Apple AirPrint, HP ePrint, Mopria Print Service
Duplex printing *	✓	Performance	
Maximum resolution *	1200 x 1200 DPI	Maximum internal memory	1536 MB
Print speed (black, normal quality, A4/US Letter) *	41 ppm	Memory slots	1
Print speed (black, normal quality, A3)	20 ppm	Internal storage capacity	500 GB
Duplex print speed (ISO/IEC 24734) mono	28 ipm	Internal memory *	1024 MB
Time to first page (black, normal)	10 s	Built-in processor	✓
Print margins (top, bottom, right, left)	2 mm	Processor frequency	800 MHz
Secure printing	✓	Sound pressure level (printing)	54 dB
Copying		Sound pressure level (scanning)	52 dB
Duplex copying *	✓	Sound power level (printing)	6.8 dB
Maximum copy resolution *	600 x 600 DPI	Design	
Copy speed (black, normal quality, A4)	41 cpm	Product colour *	Black, Grey
Maximum number of copies	9999 copies	Market positioning *	Business
Copier resize	25 - 400%	Built-in display *	✓
Auto fit function	✓	Display	LCD
		Display diagonal	20.3 cm (8")
		Control type	Touch

<b>Scanning</b>		<b>Design</b>	
Duplex scanning *	✓	Colour display	✓
Scanning *	Colour scanning	<b>Power</b>	
Optical scanning resolution *	600 x 600 DPI	Power consumption (average operating)	890 W
Maximum scan area	297 x 420 mm	Power consumption (PowerSave)	39 W
Scanner type *	Flatbed & ADF scanner	Power consumption (printing)	890 W
Scan technology	CCD	Power consumption (copying)	890 W
Scan to	E-mail, Network folder, USB, Fax	Power consumption (ready)	39 W
Scan speed (colour)	30 ppm	Power consumption (standby)	6.5 W
Scan speed (black)	50 ppm	Power consumption (sleep)	6.5 W
Image formats supported	MTIFF, JPEG, TIFF	Power consumption (off)	0.3 W
Document formats supported	XPS, PDF	Energy Star Typical Electricity Consumption (TEC)	0.653 kWh/week
Input colour depth	24 bit	AC input voltage	110 - 240 V
Greyscale levels	256	AC input frequency	50/60 Hz
<b>Fax</b>		<b>Brand-specific features</b>	
Fax resolution (black)	300 x 300 DPI	HP Auto-On/Auto-Off	✓
Fax transmission speed	3 sec/page	<b>System requirements</b>	
Modem speed	33.6 Kbit/s	Windows operating systems supported	Windows 7, Windows Vista, Windows 10, Windows 8, Windows XP
Fax memory	100 pages	Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.8 Mountain Lion, Mac OS X 10.7 Lion
Auto-redialing	✓	Linux operating systems supported	✓
Speed dialling	✓	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2012
Fax speed dialling (max numbers)	100	Other operating systems supported	Linux, Novell
Fax forwarding	✓	<b>Operational conditions</b>	
Fax broadcasting	100 locations	Operating relative humidity (H-H)	20 - 80%
Fax delayed sending	✗	Recommended humidity operating range	30 - 70%
Auto reduction	✓	Operating temperature (T-T)	10 - 32.5 °C
<b>Features</b>		<b>Certificates</b>	
Recommended duty cycle	5000 - 20000 pages per month	Certification	CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:1998+A1+A2; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries
Maximum duty cycle *	200000 pages per month		
Duplex functions *	Print, Copy, Scan	<b>Sustainability</b>	
Digital sender	✓	Sustainability compliance	✓
Number of print cartridges *	1	Sustainability certificates	EPEAT Silver, ENERGY STAR
Printing colours *	Black	Doesn't contain	Mercury
Page description languages	PCL 5, PCL 6, PDF 1.4, PostScript 3	<b>Weight &amp; dimensions</b>	
Printer fonts	PostScript, Scalable, TrueType, Windows	Width	745 mm
Number of printer fonts	105	Depth	681 mm
All-In-One-multitasking	✓	Height	1192 mm
Country of origin	Mexico, Netherlands, China	Weight	102.4 kg
HP segment	Business	<b>Packaging data</b>	
<b>Input &amp; output capacity</b>		Package width	856 mm
Total number of input trays *	5	Package depth	760 mm
Total input capacity *	4100 sheets	Package height	1553 mm
Total output capacity *	750 sheets	Package weight	122 kg
Paper tray 1 input capacity	100 sheets	<b>Packaging content</b>	
Paper tray 2 input capacity	250 sheets	Cables included	AC
Multi-Purpose tray	✓		
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	100 sheets		
Maximum number of input trays	6		
Maximum input capacity	4600 sheets		
Maximum output capacity	750 sheets		
<b>Paper handling</b>			
Maximum ISO A-series paper size *	A3		
Maximum print size	308 x 465.9 mm		

Paper handling		Packaging content	
Paper tray media types *	Thick paper, Envelopes, Rough paper, Letterhead, Bond paper, Plain paper, Card stock, Transparencies, Labels, Recycled paper	Warranty card	✓
ISO A-series sizes (A0...A9) *	A3, A4, A5	Quick installation guide	✓
ISO B-series sizes (B0...B9)	B4, B5, B6	Bundled software	Windows Installer, HP PCL 6 discrete driver, Mac SW Link to Web, [Postscript emulation driver & Installer on Web], Note: No Mac SW inbox
JIS B-series sizes (B0...B9)	B4, B5		
Custom media width	76.2 - 312 mm		
Custom media length	127 - 469.9 mm		
Paper tray media weight	60 - 199 g/m <sup>2</sup>		
Ports & interfaces		Logistics data	
Standard interfaces	Ethernet, USB 2.0	Pallet gross weight	122 g
Direct printing *	✓		
USB port	✓		
USB 2.0 ports quantity	3		
Optional connectivity	Wireless LAN		
Network		Other features	
Wi-Fi *	✗	Number of users	30 user(s)
Ethernet LAN *	✓	Pallet dimensions (W x D x H)	856 x 760 x 1553 mm
Cabling technology	10/100/1000Base-T(X)	Printer management	HP Web Jetadmin, HP Utility (Mac) Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 (64-bit); 200 MB available hard disk space; operating system compatible hardware system requirements, see <a href="http://www.micr">http://www.micr</a>
Ethernet LAN data rates	10,100,1000 Mbit/s	Recommended system requirements	
Security algorithms	PEAP, SNMPv3, EAP-TLS, IPSec, WPA2-Enterprise, SSL/TLS	Acoustic power emissions (ready)	50 dB
		Acoustic pressure emissions bystander (ready)	36 dB
		All-in-one functions	Copy, Fax, Print, Scan
		Colour all-in-one functions	Scan



0887111017185



887111017185




0887111017215



887111017215



0887758596869



887758596869



0887111017222



887111017222



0887111017192



887111017192



0887111017178



887111017178



0887758596876



887758596876



0888182819616



888182819616



0887111017208



887111017208

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.