

D-Link DBG-2000 Nuclias Cloud SD-WAN Gateway

Brand : D-Link

Product code: DBG-2000

Product name : DBG-2000 Nuclias Cloud SD-WAN Gateway

- Nuclias cloud-based remote management (1-year license included)
- Point-to-point VPN options for flexible deployments
- Security Firewall, Intrusion Prevention System (IPS)
- Dynamic Web Content Filtering, Application Control
- SD-WAN with WAN load balancing
- Zero-Touch Deployment, plug & play deployment

DBG-2000 Nuclias Cloud SD-WAN Gateway

D-Link DBG-2000 Nuclias Cloud SD-WAN Gateway. Product colour: White, LED indicators: Power, Certification: FCC, IC, RCM, VCCI. Mean time between failures (MTBF): 610802 h. Internal memory: 4096 MB, Flash memory: 16 MB. Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, Firewall throughput: 1800 Mbit/s. Console port: RJ-45



Design		Ports & interfaces	
Product colour *	White	USB 2.0 ports quantity	1
LED indicators	Power	Console port	RJ-45
Certification	FCC, IC, RCM, VCCI	Number of console ports	1
Features		Ethernet LAN (RJ-45) ports	4
Mean time between failures (MTBF)	610802 h	Management features	
Performance		Concurrent SSL VPN users (max)	200
Control display unit *	✗	Concurrent IPSec VPN connections	200
Internal memory	4096 MB	Power	
Flash memory	16 MB	Power consumption (max)	20 W
Network		Input voltage	100 - 240 V
Ethernet LAN data rates	10,100,1000 Mbit/s	Input frequency	50 - 60 Hz
Networking standards	IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Output voltage	12 V
Flow control support	✓	Weight & dimensions	
Load balancing	✓	Width	135 mm
Number of concurrent sessions (max)	200000	Depth	215 mm
Firewall throughput	1800 Mbit/s	Height	42 mm
3DES/AES throughput	0.45 Gbit/s	Weight	1.66 kg
SSL VPN throughput	0.2 Gbit/s	Operational conditions	
Sessions per second	2000	Operating temperature (T-T)	0 - 40 °C
PPTP/L2TP VPN tunnels (max)	200	Storage temperature (T-T)	-20 - 70 °C
SSL VPN tunnels (max)	200	Operating relative humidity (H-H)	5 - 95%
GRE VPN tunnels (max)	200	Storage relative humidity (H-H)	5 - 95%
Security		Sustainability	
DoS attack prevention	✓	Sustainability compliance	✓
		Sustainability certificates	CE, Low Voltage Directive (LVD)
Ports & interfaces			
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1		



0790069459825



790069459825



0790069462351



790069462351

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.