D-Link

D-Link DXS-1100-10TS network switch Managed L2 10G Ethernet (100/1000/10000) 1U Black

Brand: D-Link Product code: DXS-1100-10TS

Product name: DXS-1100-10TS



- 2 x SFP+ ports
- Energy-efficient design
- Comprehensive security features
- Traffic monitoring and bandwidth control
- Smart and flexible management
- Auto Surveillance VLAN

Managed, L2, 200 Gbps, 8 x 10G BASE-T, 2 x SFP+, VLAN

D-Link DXS-1100-10TS. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 16000 entries, Switching capacity: 200 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z. Rack mounting, Form

factor: 1U





Management features		Performance	
Switch type *	Managed	Noise level	46.4 dB
Switch layer	L2	Mean time between failures (MTBF)	585.959 h
Quality of Service (QoS) support	✓	Technical details	
ARP inspection	1	Shipping (inner) case height	38.3 cm
System event log	✓	Shipping (inner) case width	29.6 cm
Ports & interfaces		Shipping (inner) case length	52.9 cm
Basic switching RJ-45 Ethernet ports	Q	Shipping (inner) case net weight	9.67 kg
quantity *		Products per shipping (inner) case	3 pc(s)
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Pallet gross weight (air)	552.4 kg
SFP+ module slots quantity	2	Master (outer) cases per pallet (air)	40 pc(s)
Fiber optic connector	SFP+	Products per pallet (air)	120 pc(s)
		Pallet gross length	110 cm
Network		Pallet gross width	120 cm
Networking standards *	IEEE 802.1D, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z	Pallet height (air)	2.05 m
		Pallet gross weight (sea)	552.4 kg
10G support *	✓	Master (outer) cases per pallet (sea)	• • •
Copper ethernet cabling technology	10GBASE-T	Products per pallet (sea)	120 pc(s)
Port mirroring	✓	Pallet height (sea) Shipping (inner) case gross weight	2.05 m 13.3 kg
Full duplex	✓		13.3 kg
Flow control support	1	Power	
Link aggregation	✓	AC input voltage	100 - 240 V
Broadcast storm control	✓	Power consumption (max)	50.9 W
Auto MDI/MDI-X	√	Power over Ethernet (PoE)	
Spanning tree protocol VLAN support	1	Power over Ethernet (PoE) *	x
Virtual LAN features	Port-based VLAN	Operational conditions	
Number of VLANs	128	Operating temperature (T-T)	-5 - 50 °C
Data transmission		Storage temperature (T-T)	-40 - 70 °C
	200 Gbit/s	Operating relative humidity (H-H)	0 - 95%
Switching capacity * Throughput	200 GDIT/S 148.81 Mpps	Storage relative humidity (H-H)	0 - 95%
MAC address table *	16000 entries	Heat dissipation	173.57 BTU/h
Store-and-forward	✓	Weight & dimensions	
Number of queues	8	Width	441 mm
Jumbo frames support	v	Depth	210 mm
Jumbo frames	9216	Height	44 mm
		Weight	2.69 kg

Security		Packaging data	
IGMP snooping	✓	Package width	348 mm
Security algorithms	SNMP	Package depth	511 mm
Static port security	✓	Package height	91 mm
SSH/SSL support	✓	Package weight	4.14 kg
Queue scheduling algorithms	SPQ, Weighted Round Robin (WRR)	Logistics data	
Design		Harmonized System (HS) code	85176990
Rack mounting *	✓		
Form factor	1U		
Product colour	Black		
Number of fans	2 fan(s)		
Performance			
Flash memory	128 MB		





790069422836

0790069422836

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.