



TP-Link AX3000 Indoor/Outdoor WiFi 6 Access Point

Brand : TP-Link

Product code: EAP650-OUTDOOR

Product name : AX3000 Indoor/Outdoor WiFi 6 Access Point

AX3000, Wi-Fi 6 802.11ax/ac/n/g/b/a, 2.4/5 GHz, IP67, 280.4 x 106.5 x 56.8 mm

TP-Link AX3000 Indoor/Outdoor WiFi 6 Access Point. Maximum data transfer rate: 1000 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x,.... Security algorithms: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise, Service Set Identifier (SSID) features: Multiple SSIDs, SSID broadcast on/off. Placement: Pole, Wall, Product colour: White, International Protection (IP) code: IP67. Antenna type: Internal, Antenna direction type: Omni-directional. Width: 280.4 mm, Depth: 106.5 mm, Height: 56.8 mm



Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Design	
6 GHz *	✗	Placement *	Pole, Wall
Maximum data transfer rate *	1000 Mbit/s	Product colour *	White
Ethernet LAN data rates	10,100,1000 Mbit/s	International Protection (IP) code	IP67
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at	Reset button	✓
Cabling technology	10/100/1000Base-T(X)	Certification	CE, FCC, RoHS
Number of users	250 user(s)	Antenna	
MIMO	✓	Antenna type *	Internal
MIMO type	Multi User MIMO	Antenna direction type	Omni-directional
Fit AP mode features	Mesh networking	Weight & dimensions	
VLAN support	✓	Width	280.4 mm
Quality of Service (QoS) support	✓	Depth	106.5 mm
Security		Height	56.8 mm
Security algorithms *	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise	Operational conditions	
MAC address filtering	✓	Operating relative humidity (H-H)	10 - 90%
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast on/off	Operating temperature (T-T)	-30 - 70 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN (RJ-45) ports *	1	Storage relative humidity (H-H)	5 - 90%



4897098682098



4897098683552



0840030703553



840030703553

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.