

Intel PRO/1000 PT Server Adapter Internal 1000 Mbit/s

Brand : Intel

Product code: EXPI9400PT

Product name : PRO/1000 PT Server Adapter



Intel PRO/1000 PT Server Adapter 10BASE-T,100BASE-TX,1000BASE-T / RJ-45
 Intel PRO/1000 PT Server Adapter. Internal. Connectivity technology: Wired, Host interface: PCI Express.
 Maximum data transfer rate: 1000 Mbit/s



Ports & interfaces		Other features	
Connectivity technology *	Wired	Cable type	Category-5 up to 100m
Host interface *	PCI Express	Market segment	Server
Ethernet LAN (RJ-45) ports	1	Power requirements	1A, +5VDC
Network		Management protocols	DMI 2.0, WMI & SNMP
Maximum data transfer rate *	1000 Mbit/s	Intel Virtual Machine Device Queues (VMDq)	✗
Networking standards *	IEEE 802.3ab	PCI-SIG* SR-IOV Capable	✗
Ethernet LAN	✓	On-chip QoS and Traffic Management	✗
Ethernet LAN data rates	10,100,1000 Mbit/s	Intel Flexible Port Partitioning	✗
Cabling technology	10/100/1000BaseT(X)	Speed & slot width	2.5 GT/s, x1 Lane
Wi-Fi	✗	Intelligent Offloads	✓
Wake-on-LAN ready	✓	iWARP/RDMA	✗
Full duplex	✓	Intel Ethernet Power Management	✗
Maximum operating distance	100 m	Intel Virtualization Technology for Connectivity (VT-c)	✗
LAN controller	Intel 82572GI	Interface type	PCIe v1.0a (2.5GT/s)
Design		Storage Over Ethernet	iSCSI, NFS
Internal *	✓	Born on date	Q4'05
Plug and Play	✓	Launch date	2005-10-01T00:00:00
LED indicators	Link	Network interface card cable medium	Copper
Certification	FCC B, UL, CE, VCCI, BSMI, CTICK, MIC	Network interface card type	Server
Power		Product brief URL	http://www.intel.com/Assets/PDF/prodbrief/pro1000_pt_server_adapter.pdf
Power consumption (typical)	3.3 W	Product name	Intel PRO/1000 PT Server Adapter
System requirements		Product type	13
Compatible operating systems	FreeBSD Microsoft Windows 2000 Microsoft Windows Server 2003 Novell NetWare SCO OpenServer SunSoft Solaris Red Hat Linux 5.x OpenUNIX 8	Status	End of Life
Operational conditions		Thermal Design Power (TDP)	3.3 W
Operating temperature (T-T)	0 - 55 °C	Number of QPI links	Single
Sustainability		Ethernet adapter ARK ID	50497
Sustainability certificates	RoHS	Bracket height	Low-Profile (LP) / Full-Height (FH)
Weight & dimensions		Product family	Intel Gigabit server adapter
Width	22 mm	Product series	Intel PRO/1000 PT
Depth	129 mm	Product codename	Glyndon
Height	120 mm		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-JAN-2024. Prints or copies of Information are only valid on the printed Publication date