Belkin AC 1000 DB wireless router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Black

Brand : Belkin Product code: F9K1112AS

Product name: AC 1000 DB

AC 1000 DB Wi-Fi Dual-Band AC+ Gigabit - 2.4/5 GHz, 802.11a/b/g/n/ac, Gigabit Ethernet, 650 Mbps Max, 1x WAN, 4x RJ-45, 2x USB, Black

Belkin AC 1000 DB. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 650 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Cabling technology: 10/100/1000Base-T(X). Security algorithms: WEP, WPA, WPA2, Authentication method: SSID. Switching protocols: Ethernet, Routing protocols: IP, Management protocols: HTTP. Product colour: Black





WAN connection		Security	
Ethernet WAN *	✓	Network address translation (NAT)	✓
Wireless LAN features		Protocols	
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) * Wi-Fi standards Number of WLAN connections (max) Network Ethernet LAN * Ethernet LAN interface type *	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) 650 Mbit/s 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n) 32 Gigabit Ethernet	Switching protocols Routing protocols Management protocols Design Product colour LED indicators Packaging content Cables included	Ethernet IP HTTP Black ✓ LAN (RJ-45)
Ethernet LAN data rates Cabling technology Networking standards	10,100,1000 Mbit/s 10/100/1000Base-T(X) IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	AC adapter included Antenna Antenna design * Detachable antenna(s)	Internal ×
Mobile network		Features	
	× ×	Plug and Play Operational conditions	×
	×	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 65 °C 10 - 85%
Ports & interfaces		System requirements	
Ethernet LAN (RJ-45) ports * DC-in jack	4	Windows operating systems supported	1
Management features		Mac operating systems supported	✓
Web-based management Quality of Service (QoS) support Reset button Security	1 1 1	Other features Mobile network connection WLAN data transfer rates supported USB ports quantity	X 11,54,300,650 Mbit/s 2
Security algorithms	WEP, WPA, WPA2	Number of users	4 user(s)

Security		Other features	
Authentication method	SSID	Input current	0.8 A
Firewall	✓	Frequency band	2.4 & 5
Stateful Packet Inspection (SPI)	✓	Rack mounting	×
		xDSL connection	×

