

## NETGEAR 8 Port PoE Gigabit Ethernet Plus Switch (GS308EP)

**Brand :** NETGEAR

**Product code:** GS308EP-100NAS

**Product name :** 8 Port PoE Gigabit Ethernet Plus Switch (GS308EP)



8-Port Gigabit Ethernet PoE+ Plus Switch (62W)

[NETGEAR 8 Port PoE Gigabit Ethernet Plus Switch \(GS308EP\):](#)

### 300 Series SOHO Plus (GS308EP)

The NETGEAR 8-Port Gigabit Ethernet PoE+ Plus Switch delivers essential business networking features and powers PoE+ devices like VoIP phones, IP cameras, and more.

NETGEAR 8 Port PoE Gigabit Ethernet Plus Switch (GS308EP). Switch type: Managed, Switch layer: L2/L3.

Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45

Ethernet ports quantity: 8. Full duplex. MAC address table: 4000 entries, Switching capacity: 16 Gbit/s.

Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x.

Power over Ethernet (PoE)



Management features		Security	
Switch type *	Managed	Loop protection	✓
Switch layer	L2/L3	Multicast features	
Quality of Service (QoS) support	✓	Multicast support	✓
Web-based management	✓	Design	
MIB support	✓	Product colour	Black
Ports & interfaces		LED indicators	✓
Basic switching RJ-45 Ethernet ports quantity *	8	Certification	CE mark, commercial, FCC Part 15 class B, CE/EN55032/24, VCCI, ACMA, CSA safety KC, BSMI
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) ports quantity	8
10G support *	✗	Power over Ethernet plus (PoE+) ports quantity	8
Port mirroring	✓	Operational conditions	
Full duplex	✓	Operating temperature (T-T)	0 - 40 °C
Flow control support	✓	Storage temperature (T-T)	-20 - 70 °C
Link aggregation	✓	Operating relative humidity (H-H)	0 - 90%
Broadcast storm control	✓	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN data rates	1000 Mbit/s	Operating altitude	0 - 3000 m
VLAN support	✓	Weight & dimensions	
Data transmission		Width	158 mm
Switching capacity *	16 Gbit/s	Depth	101 mm
MAC address table *	4000 entries	Height	27 mm
Jumbo frames support	✓	Packaging data	
Jumbo frames	9216	Quick start guide	✓
Security		User guide	✓
DHCP features	DHCP client	Manual	✓
IGMP snooping	✓		



0606449153026



606449153026

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.