



HP LaserJet Color 5550dn Printer Colour 600 x 600 DPI A3

Brand : HP

Product family: LaserJet

Product code: Q3715A

Product name : Color LaserJet 5550dn Printer



Color LaserJet 5550dn 28 ppm A4, 14 ppm A3, 600 x 600 dpi, HP ImageREt 3600, 2 paper trays, HP Jetdirect 620n Fast Ethernet Print Server, Duplex print

HP LaserJet Color 5550dn Printer Colour 600 x 600 DPI A3:

Create impressive colour documents easily with this simple-to-use, wide-format laser printer. With its proven design, high performance and flexible features the HP Color LaserJet 5550 series printer meets the needs of dynamic workgroups.

- Delivers a perfect blend of brilliant print quality and great performance.
- Powerful wide-format colour performance for versatile workgroups.
- Experience office printing as it's meant to be.

HP LaserJet Color 5550dn Printer. Print technology: Laser, Colour. Number of print cartridges: 4, Maximum duty cycle: 120000 pages per month. Maximum resolution: 600 x 600 DPI. Maximum ISO A-series paper size: A3. Print speed (black, normal quality, A4/US Letter): 27 ppm, Duplex printing. Network ready



Printing		Other features	
Print speed (colour, normal quality, A4/US Letter)	28, 27	Standard media sizes	A3, A4, A5, A6, B4 (JIS), B5, B5 (JIS), B6, C5, DL, double postcard (JIS), Executive (JIS), RA3
Print speed (black, draft quality, A4/US Letter)	28 ppm	Memory upgrade	0.544 GB
Colour *	✓	Print margin bottom (A4)	5 mm
Print technology *	Laser	Print margin left (A4)	5 mm
Duplex printing *	✓	Print margin right (A4)	5 mm
Maximum resolution *	600 x 600 DPI	Print margin top (A4)	5 mm
Print speed (black, normal quality, A4/US Letter) *	27 ppm	Typefaces	80 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); additional font solutions available via third-party flash memory cards
Print speed (colour, draft quality, A4/US Letter)	28 ppm	Media weights by paper path	Tray 1: up to 200 g/m ² ; Tray 2, 3, 4, 5: up to 120 g/m ²
Print speed (black, normal quality, A3)	14 ppm	Recommended media weight	Tray 1: 60 - 200; Tray 2, 3, 4, 5: 60 - 120
Print speed (colour, normal quality, A3)	14 ppm	Standard output capacity for envelopes	40 sheets
Warm-up time	120 s	Minimum system requirements	Microsoft Windows 7 ready. For more information go to http://go/windows7 . Some features may not be available. Windows Vista: 1 GHz processor, 512 MB RAM (check User's Guide for minimum hard disk space); Windows 2000: 300 MHz processor, 64 MB RAM; Windows XP: 233 MHz processor, 64 MB RAM; for all systems: 180 MB available hard disk space, CD-ROM drive or Internet connection, IEEE-1284 parallel port
Time to first page (black, normal)	16 s	Envelope feeder	✗
Features		Printer management	HP Web Jetadmin, HP Embedded Web Server, HP eToolbox
Maximum duty cycle *	120000 pages per month	Acoustic power emissions	6.6 B(A), printing A4 monochrome from standard tray at full engine speed
Number of print cartridges *	4	Power requirements	100 - 240 VAC (- 10/+ 6%), 50/60 Hz (+/-2 Hz)
Input & output capacity		Print quality (colour, best quality)	600 DPI
Total input capacity *	600 sheets		
Total output capacity *	250 sheets		
Paper tray 2 input capacity	500 sheets		
Maximum input capacity	2100 sheets		
Maximum output capacity	250 sheets		
Paper handling			
Maximum ISO A-series paper size *	A3		
Paper tray media types *	Envelopes, Glossy paper, Labels, Plain paper, Transparencies		
ISO A-series sizes (A0...A9) *	A3, A4, A5		
JIS B-series sizes (B0...B9)	B4, B5		
Duplex media weight	60 - 120 g/m ²		

Paper handling		Other features	
Media types supported	Paper (extra heavy, glossy, heavy, heavy glossy, high gloss images, intermediate, light, plain, recycle, tough), envelopes, labels, cardstock, transparencies	Duplex print options	Automatic (standard)
Media size (tray 1)	Letter, letter-R, legal, executive, tabloid (11 x 17 in), ledger, 16K, 8K, A3, A4, A4-R, A5, envelope (No. 10, DL, C5, B5, Monarch), B4-JIS, B5-JIS, executive-JIS, double postcard-JIS, 12 x 18 in, 8.5 x 13 in, A6, B6, RA3, statement, 76.2 x 98 to 306 x 470 mm	Print speed (colour, best quality, A4)	28 ppm
Media weight (tray 1)	60 - 200 g/m ²	Print speed (black, best quality, A4)	28 ppm
Network		Colour printing technology	HP ImageREt 3600
Network ready	✓	Paper handling	100-sheet multipurpose tray 1, 500-sheet input tray 2, optional 500-sheet input trays 3/4, 250-sheet output bin
Supported network protocols (IPv4)	Via HP Jetdirect print servers: TCP/IP, IPX/SPX, AppleTalk, Apple Rendezvous compatible, DLC/LLC, Auto-IP, IP Direct Mode, NDS, Bindery, NCP, NDPS, iPrint, Telnet, SLP, IGMP, BOOTP/DHCP, WINS, SNMP v 1 and v 2c, HTTP; may require software from the NOS vendor or third-party vendor: LPD, FTP Printing, IPP	Electromagnetic compatibility	CISPR 22: 1997/EN 55022: 1998 Class B, EN 61000-3-2:2000, EN 61000-3-3: 1995, EN 55024: 1998, FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly
Performance		Standard input trays	2
Internal memory *	160 MB	Networking features	HP Jetdirect Fast Ethernet embedded print server Yes, via HP Jetdirect internal Fast Ethernet, Gigabit Ethernet, 802.11b wireless
Maximum internal memory	544 MB	Print quality (black, best quality)	600 x 600 DPI
Built-in processor	✓	Wireless option type	Optional, enabled with purchase of a hardware accessory
Processor model	MIPS RISC	Standard output capacity for transparencies	250 sheets
Processor frequency	533 MHz	Driver updates	OS/2, UNIX, Linux; basic printing support for DOS; current drivers and software are available from the Internet at /support/clj5550
Power		Duplex supported media size	A3, A4, A5, B4-JIS, B5-JIS
Power consumption (standby)	93 W	Media handling	Sheetfed
Power consumption (PowerSave)	28 W	Memory technology	Memory Enhancement technology (MEt)
Power consumption (off)	0.3 W	Control panel	LCD control panel display with 4 lines of text and capable of showing graphic animations; 3 LED status lights; Cancel job, Pause/Resume, Help (appears as a question mark), Select (appears as a checkmark), Up arrow, Down arrow, Back arrow buttons
System requirements		Maximum paper trays	5
Minimum system requirements for Macintosh	Mac OS X v10.2.8, 10.3, 10.4, 10.5, 10.6; 4 MB RAM; 160 MB available hard disk space; USB port or AppleTalk, Bonjour connectivity solution	Media size (tray 2)	A4, A3, A5, B4-JIS, B5-JIS
Operational conditions		Media type and capacity (tray 2)	sheets: 500
Operating temperature (T-T)	15 - 27 °C	Media weight (tray 2)	Up to 120 g/m ²
Storage temperature (T-T)	0 - 35 °C	Media weight (tray 3)	Up to 120 g/m ²
Operating relative humidity (H-H)	10 - 70%	Paper handling optional/input	500-sheet input trays (3), printer stand
Storage relative humidity (H-H)	10 - 90%	Paper handling standard/input	100-sheet multipurpose tray, 500-sheet input Tray 2, automatic two-sided printing
Operating temperature (T-T)	63 - 77 °F	Paper handling standard/output	250-sheet face-down output bin
Sustainability		Power consumption (active)	623 W
Sustainability certificates	ENERGY STAR		
Weight & dimensions			
Maximum dimensions (W x D x H)	577 x 1550 x 640 mm		
Pallet dimensions (W x D x H)	1010 x 780 x 822 mm		
Weight	51.8 kg		
Dimensions (WxDxH)	577 x 704 x 640 mm		
Packaging data			
Package weight	85 kg		
Packaging content			
Bundled software	Print drivers and installation software on CD-ROM: HP PCL 6, HP PostScript Level 3 emulation (32-bit drivers only), HP PCL 5c (provided on add printer install)		

Logistics data		Other features	
Pallet gross weight	95 kg		
Products per pallet	1 pc(s)		
Other features			
Additional paper trays	500-sheet input tray 4 and feeder		
Print quality (black, draft quality)	600 DPI		
Print quality (black, normal quality)	600 DPI		
Power supply type	110~220V		
Recommended operating temperature range (T-T)	15 - 25 °C	Safety	Argentina (TUV S Mark-Rs.92/98/Ds.1009/98), Australia (AS/NZ 3260), Canada (cUL-CAN/CSA C22.2 No.60950-00), China (GB4943), Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN60950-IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV-EN60950-IEC 60825-1), Hungary (MEEI- IEC 60950-IEC 60825-1), Japan Radio Law, Lithuania (LS- IEC 60950-IEC 60825-1), Mexico (NOM NYCE-NOM 019 SCFI), Poland (B Mark- IEC 60950-IEC60825-1), (Russia (GOST- R50377), Slovakia (IEC 60950-IEC60825-1), Slovenia (SQI- IEC 60950-EN60825-1), South Africa (IEC 60950-IEC60825-1), USA (UL-UL 60950, FDA-21 CFR Chapter 1 Subchapter J for lasers); Class 1 Laser/LED Product
Mac compatibility	✓		
I/O ports	1 USB, 1 parallel, 2 EIO, 1 Ethernet, 1 Jetlink		
Custom media sizes	Tray 1: 76 x 127 to 306 x 470 mm; automatic two-sided printing, Tray 2, 3, 4, 5: 148 x 210 to 297 x 431.8 mm Tray 1: 3 x 5 to 12.05 x 18.5 in; automatic two-sided printing, Trays 2, 3, 4, 5: 5.8 x 8.3 to 11.7 x 17 in		
		Security management description	Management security: SNMP v 3, SSL/TLS (HTTPS), 802.1x authentication; wireless network security: WPA (Wi-Fi Protected Access), WEP encryption (40/64- and 128-bit), 802.1x authentication (EAP-PEAP, LEAP, EAP-TTLS, EAP-TLS, EAP-MD5) with RADIUS servers
		Upgrade type	Color tables, formatter firmware, software drivers, 500-sheet input trays (1, 2, or 3), hard disk, printer stand, memory
		Downloadable software	Microsoft Windows 2000, XP (32-bit and 64-bit drivers), Server 2003 (32-bit and 64-bit drivers); Apple Macintosh OS 9 and later, Mac OS X v.10.1 and later
		Compatible operating systems	Microsoft Windows 2000, XP Home, XP Professional, Windows Vista Ready, Windows Server 2003 (32/64 bit); Mac OS 9
		Package dimensions (W x D x H)	995.7 x 767.1 x 823 mm (39.2 x 30.2 x 32.4")
		Pallet dimensions (W x D x H) (imperial)	1010.9 x 779.8 x 823 mm (39.8 x 30.7 x 32.4")
		Pallet weight (imperial)	94.8 kg (208.9 lbs)
		Product dimensions when open (LxWxD)	57.7 cm (22.7")
		Weight (imperial)	114 lb
		Acoustic pressure emissions bystander (active, print, copy or scan)	49 dB(A)
		Duplex binding	✓
		First page out (black&white, A4, ready)	16 s
		First page out (black&white, letter, ready)	16 s
		First page out (black&white, letter, sleep)	41 s
		Media sizes supported (imperial)	Letter, legal, statement, executive, 11 x 17 in, ledger, envelopes (No. 10, Monarch)
		Operating altitude (imperial)	10000 ft
		Package weight (imperial)	84.8 kg (187 lbs)
		Print speed (black, best quality, letter)	< 27
		Print speed (colour, best quality, letter)	< 27
		Size (imperial)	57.7 cm (22.7")
		Recommended media weight (duplex, imperial)	16 to 32 lb

Other features

Package dimensions (WxDxH) 995 x 767 x 822 mm



0829160126951



829160126951



0829160126852



829160126852



0882780497139



882780497139



0829160126913



829160126913



0829160126906



829160126906



4053162672512




0829160126869



829160126869




0829160126876



829160126876



0829160126883



829160126883



0829160126890



829160126890



0829160582566



829160582566




0829160530512



829160530512



0829160126920



829160126920




0829160126937



829160126937



0829160126944



829160126944



0829160126968



829160126968



0884420111085



884420111085




0829160126975



829160126975




0829160126982



829160126982




0829160126999



829160126999



0829160127002



829160127002



0829160127019



829160127019



0884420111078



884420111078




0829160126807



829160126807




0829160126760



829160126760




0829160126777



829160126777



0829160126784



829160126784



0829160126791



829160126791



0829160126814



829160126814



0829160126821



829160126821



0829160485515



829160485515



0829160126838



829160126838



0829160126845



829160126845

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.