



# HP LaserJet P3005x Printer 1200 x 1200 DPI A4



Brand : HP

Product family: LaserJet

Product code: Q7816A

Product name : LaserJet P3005x Printer

Enable productivity with fast, flexible monochrome HP LaserJet printing. Accomplish more with speeds of up to 33 ppm. Enjoy easy connectivity, integrated full-featured networking, paper handling options and best print quality with true 1200 dpi.

## HP LaserJet P3005x Printer 1200 x 1200 DPI A4:

Count on solid performance with the reliable HP LaserJet P3005 Printer series that's built for productivity. Get more done with a fast first page out in 9.5 seconds even from Powersave mode, and speeds of up to 33 ppm. HP print cartridge technology [p1] works with the printing system to deliver professional quality business documents with true 1200 dpi at full engine speed. Easy connectivity and integrated full-featured networking [p2] mean you can share the printer without interruption.



ABU - United Kingdom - UK English localization

Printing		Other features	
Colour *	✗	Typefaces	103
Maximum resolution *	1200 x 1200 DPI	Media weights by paper path	60 - 200 g/m <sup>2</sup> ; 60 - 120 g/m <sup>2</sup>
Print speed (black, normal quality, A4/US Letter) *	33 ppm	Standard output capacity for envelopes	10 sheets
Time to first page (black, normal)	9.5 s		
Economical printing	✓		
Features			
Maximum duty cycle *	100000 pages per month	Minimum system requirements	Microsoft Windows 2000, XP Home, XP Professional: 1 GHz processor, 512 MB RAM (Windows Vista™, check user guide for minimum hard drive space); 333 MHz processor, 64 MB RAM; Server 2003: 550 MHz processor, 128 MB RAM; 200 MB of available hard disk space (all systems)
Number of print cartridges *	1		
Input & output capacity			
Total input capacity *	1100 sheets	Envelope feeder	✗
Total output capacity *	250 sheets	Printer management	HP Web Jetadmin, HP LaserJet Utility, HP Embedded Web Server, Easy Printer Care
Maximum input capacity	1100 sheets	Acoustic power emissions	6.5 B(A)
Maximum output capacity	250 sheets	Acoustic pressure emissions	51 dB
Paper handling			
Maximum ISO A-series paper size *	A4	Power requirements	100 - 127V / 220 - 240V, 50/60 Hz (+/- 2 Hz)
Maximum print size	207.4 x 347.1 mm	Duplex print options	Automatic (standard)
Paper tray media types *	Bond paper, Envelopes, Labels, Plain paper, Recycled paper, Transparencies	Print speed (black, best quality, A4)	33 ppm
ISO A-series sizes (A0...A9) *	A4, A5		
Non-ISO print media sizes	Executive, Legal, Letter	Electromagnetic compatibility	CISPR 22: 1993+A1+A2/EN 55022: 1994+A1+A2 Class B, EN 61000-3-2: 2000, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part 15 Class B (US), ICES-003, Issue 4 (Canada), GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC with CE Marking (EU)
Duplex media weight	60 - 120 g/m <sup>2</sup>		
Media types supported	Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough), envelopes, labels, cardstock, transparencies, user-defined	Standard input trays	3
Media size (tray 1)	76 x 127 - 216 x 356 mm	Networking features	Ethernet, Fast Ethernet
Media weight (tray 1)	60 - 200 g/m <sup>2</sup>	Print quality (black, best quality)	1200 x 1200 DPI
Network			
Network ready	✓	Wireless option type	Optional, enable via I/O ports with purchase of wireless adapter
		Standard output capacity for transparencies	75 sheets
		Driver updates	Most recent printer drivers and software for all supported operating systems available at <a href="http://www.hp.com/support/LJP3005">http://www.hp.com/support/LJP3005</a>
		Duplex supported media size	A4, letter, legal, executive (JIS)
		Media handling	Sheetfed

Network		Other features	
Supported network protocols (IPv4)	TCP/IP, IPX/SPX, AppleTalk, DLC/LLC, IP Direct Mode, LPD2, FTP Printing (may require software from the NOS or third-party vendor), IPP2, Netware NDS, Bindery, NDPS, iPrint, Telnet, SLP, IGMP, BOOTP/DHCP, WINS, SNMP, HTTP, Auto-IP, Apple Bonjour Compatible (Mac OS X 10.2.4 and higher)	Memory technology	Memory Enhancement technology (MET) Graphical display with up to 2 lines of text; Help button to provide information about the message on the display; Back button to back up in menus or exit menus; Pause/Resume button to pause and resume printing; Up Arrow button to navigate to previous item in list or increase value of numerical items; Down Arrow button to navigate to next item in list or decrease value of numerical items; Select button to open and navigate menus, clear error conditions, save selected items, and perform action highlighted; Cancel Job button to cancel print jobs; Ready, Data, and Attention lights to provide status
Performance		Control panel	
Internal memory *	80 MB		
Maximum internal memory	320 MB		
Built-in processor	✓		
Processor model	Motorola ColdFire V5		
Processor frequency	400 MHz		
Power		Maximum paper trays	3
Power consumption (PowerSave)	9 W	Media size (tray 2)	A4, A5, B5 (JIS), letter, legal, executive
Power consumption (off)	0.2 W	Media type and capacity (tray 2)	500
System requirements		Media weight (tray 2)	60 - 120 g/m <sup>2</sup>
Minimum system requirements for Macintosh	Mac OS X v10.2.8, 10.3.9, 10.4.3; 200 MB available hard disk space; USB (compatible with USB 2.0 specifications) port or IEEE 1284-B compliant parallel port; CD-ROM drive	Media weight (tray 3)	60 - 120 g/m <sup>2</sup>
Operational conditions		Paper handling standard/input	100-sheet multi-purpose tray, 500-sheet input tray, automatic duplex printing
Operating temperature (T-T)	15 - 32.5 °C	Paper handling standard/output	250-sheet output bin, 100-sheet rear output bin
Storage temperature (T-T)	-20 - 40 °C	Power consumption (active)	600 W
Operating relative humidity (H-H)	10 - 80%		IEC 60950 (International), EN 60950 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A11+A2 Class 1, 21 CFR Ch. 1/SubCh. J (Class 1 Laser/LED Device)
Storage relative humidity (H-H)	10 - 90%		GB4943-2001, Low Voltage Directive 73/23/EEC with CE Marking (Europe)
Sustainability		Safety	
Sustainability certificates	ENERGY STAR		Advanced security: SNMPv3, SSL/TLS (HTTPS), 802.1X Authentication (EAP-PEAP, EAP-TLS), IPsec (requires Jetdirect 635n)
Weight & dimensions		Security management description	Windows Installer, HP PCL 5e driver, HP PCL 6 driver, HP postscript level 3 emulation driver, HP Web Jetadmin, Macintosh installer, Macintosh postscript driver, PostScript Printer Description (PPD) files, IBM drivers, OS/2 PCL 5 or PCL 6 printer driver, OS/2 PS printer driver, UNIX model scripts, Linux drivers, HP OpenVMS drivers
Maximum dimensions (W x D x H)	425 x 780 x 474 mm		OS/2, UNIX, Linux, HP OpenVMS Windows 98 SE, 2000, Me, XP Home, XP Professional, Server 2003; Mac OS v10.2.8, 10.3.9, 10.4.3
Pallet dimensions (W x D x H)	1200 x 1000 x 2283 mm		
Weight	21.3 kg		
Dimensions (WxDxH)	425 x 410 x 474 mm		
Packaging data		Downloadable software	
Package weight	26.4 kg		
Packaging content		Compatible operating systems	
Bundled software	Print drivers and installation software on CD-ROM; Microsoft Windows Installer; Macintosh Installer; HP PCL 5e, HP PCL 6 print drivers for Windows 2000, XP Home, XP Professional; HP postscript level 3 emulation for Windows 2000, XP Home, XP Professional		
Logistics data		Package dimensions (W x D x H)	600.2 x 496.1 x 711.2 mm (23.6 x 19.5 x 28")
Pallet gross weight	340.1 kg	Pallet dimensions (W x D x H) (imperial)	1201.4 x 1000.8 x 2301.2 mm (47.3 x 39.4 x 90.6")
Layers per pallet	8 pc(s)	Pallet weight (imperial)	339.4 kg (748.2 lbs)
Products per pallet	12 pc(s)	Product dimensions when open (LxWxD)	42.4 cm (16.7")
Other features		Weight (imperial)	Without toner cartridge 47 lb
Print quality (black, draft quality)	600 DPI	Acoustic pressure emissions bystander (active, print, copy or scan)	51 dB(A)
Standard input capacity for transparencies	75	Duplex binding	✗
Print quality (black, normal quality)	600 DPI	First page out (black&white, A4, ready)	9.5 s
Recommended operating temperature range (T-T)	15 - 32.5 °C		
Mac compatibility	✓		
I/O ports	1 x USB 2.0 1 x EIO		

Other features		Other features	
Custom media sizes	76 x 127 - 216 x 356 mm	First page out (black&white, letter, ready)	9.5 s
Standard media sizes	A4, A5, B5 (JIS), letter, legal, executive	First page out (black&white, letter, sleep)	9.5 s
Print margin bottom (A4)	5 mm	Media sizes supported (imperial)	Letter, legal, executive, 8.5 x 13 in, envelopes
Print margin left (A4)	5 mm	Operating altitude (imperial)	10000 ft
Print margin right (A4)	5 mm	Package weight (imperial)	26.4 kg (58.1 lbs)
Print margin top (A4)	5 mm	Print speed (black, best quality, letter)	Up to 35 ppm
		Size (imperial)	42.4 cm (16.7")
		Standard input capacity for envelopes	10 sheets
		Acoustic power emissions (ready)	Inaudible
		Acoustic pressure emissions bystander (ready)	Inaudible
		Maximum input capacity (tray 1)	100 sheets
		SureSupply connection type	Direct and Network
		SureSupply supported	✓
		Typical electricity consumption (TEC) number	2.642 kWh/Week
		Recommended media weight (duplex, imperial)	16 to 32 lb
		UNSPSC-code	43212105
		Package dimensions (WxDxH)	600 x 500 x 720 mm



0882780567405




882780567405



8827805675118



0882780567511



882780567511



0882780567436



882780567436



0882780567320



882780567320




0882780567443



882780567443



0882780567528




882780567528



5711045506987



0882780567412



882780567412



0999999417756



999999417756



0882780567573



882780567573



0882780567481



882780567481



0882780980891



882780980891



0882780567948



882780567948



0882780567955



882780567955



0882780567962



882780567962



0882780567979



882780567979



0882780567337



882780567337



0882780567344



882780567344



0882780567351



882780567351




0882780567368



882780567368



0882780567375



882780567375



0882780567382



882780567382



0882780567399



882780567399



0882780567429



882780567429



0882780567450



882780567450



0883585002382



883585002382



0882780567467



882780567467



0882780567498



882780567498



0882780567504



882780567504



0882780567535



882780567535



0882780567542



882780567542



0882780567559



882780567559



0882780567566



882780567566



0882780567474



882780567474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.