

## Seagate SV35 Series 250GB 3.5" Ultra ATA/100 3.5" Ultra-ATA/100

**Brand :** Seagate

**Product family:** SV35 Series

**Product code:** ST3250820AV

**Product name :** 250GB 3.5"  
Ultra ATA/100

250GB 3.5" Ultra ATA/100

[Seagate SV35 Series 250GB 3.5" Ultra ATA/100 3.5" Ultra-ATA/100:](#)

The Seagate SV35 Series hard drive is the first drive specifically engineered and optimized for digital video recording in security and surveillance applications.



### Increased SDVR Performance

- Increased video data rates (480Mb/s) enable higher-performance video recording.
- Optimized to record multiple, simultaneous video streams.
- Engineered to maintain high video data integrity.

### Higher Reliability

- Designed for 24x7 operation and high write duty cycles.
- 1,000,000 hours MTBF in 24x7 video surveillance applications.
- Fewer moving parts.
- Lower power consumption.
- Reduced heat generation.

### Tailored for the Video Surveillance Industry

- Technical and marketing support infrastructure dedicated to video surveillance customers.
- Second-generation SDVR drive — evolving with emerging industry requirements.
- Advanced application design and technical advice available through Seagate Design Service Centers in U.S. and Singapore.

Features		Operational conditions	
HDD size *	3.5"	Operating temperature (T-T)	0 - 600 °C
HDD capacity *	250 GB	Storage temperature (T-T)	-40 - 70 °C
HDD speed *	7200 RPM	Operating relative humidity (H-H)	5 - 90%
Interface *	Ultra-ATA/100	Storage relative humidity (H-H)	5 - 95%
Type *	HDD	Operating altitude	-60.96 - 3048 m
Component for *	Surveillance system	Non-operating altitude	-60.96 - 12192 m
Storage drive buffer size	8 MB	Operating shock	63 G
Read seek time	17 ms	Non-operating shock	300 G
Write seek time	14 ms	<b>Weight &amp; dimensions</b>	
Bytes per sector	512	Width	101.6 mm
Start/stop cycles	50000	Height	26.1 mm
Mean time between failures (MTBF)	1000000 h	Depth	147 mm
Windows operating systems supported	✓	Weight	600 g
Linux operating systems supported	✓	<b>Other features</b>	
<b>Power</b>		Drive devices burst data transfer rate (PIO)	0-4
Operating voltage	5 / 12 V	Drive devices burst data transfer rate (Ultra DMA)	0-6
		Drive ready time	7 s

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-JAN-2024. Prints or copies of Information are only valid on the printed Publication date