

## Seagate Barracuda 7200.9 400GB PATA 3.5" Parallel ATA



**Brand :** Seagate

**Product family:** Barracuda

**Product code:** ST3400833A

**Product name :** 7200.9 400GB  
PATA

3.5", 400GB, PATA, 16MB Cache, 7200RPM

[Seagate Barracuda 7200.9 400GB PATA 3.5" Parallel ATA:](#)

- 7,200-RPM spindle speed
- High instantaneous (burst) data transfer rates (up to 100 Mbytes per second) using Ultra DMA mode 5.
- Tunneling Magnetoresistive (TMR) recording heads provide the drives with increased areal density.
- State-of-the-art cache and on-the-fly error-correction algorithms.
- Full-track multiple-sector transfer capability without local processor intervention.
- Quiet operation.
- 350 Gs nonoperating shock.
- SeaTools diagnostic software performs a drive self-test that eliminates unnecessary drive returns.
- Support for S.M.A.R.T. drive monitoring and reporting.
- Support for Read Multiple and Write Multiple commands.
- Support for autodetection of master/slave drives that use cable select (CSEL).

Seagate Barracuda 7200.9 400GB PATA. HDD size: 3.5", HDD capacity: 400 GB, HDD speed: 7200 RPM

Features		Operational conditions	
HDD size *	3.5"	Operating altitude	-60.96 - 3048 m
HDD capacity *	400 GB	Non-operating altitude	-60.96 - 12192 m
HDD speed *	7200 RPM	Operating shock	63 G
Interface *	Parallel ATA	Non-operating shock	300 G
Type *	HDD	Weight & dimensions	
Storage drive buffer size	16 MB	Width	101.6 mm
HDD number of cylinders	16383	Height	26.1 mm
Read seek time	11 ms	Depth	147 mm
Write seek time	12 ms	Weight	710 g
Track to track seek time	1 ms	Packaging data	
Average latency	4.16 ms	Quantity	1
Bytes per sector	512	Other features	
Start/stop cycles	50000	Wi-Fi	✗
Power		Ethernet LAN	✗
Operating voltage	5 / 12 V	Product colour	Black
Start-up current	2.9 A	Internal	✗
Operational conditions		Maximum data transfer rate	815.2 Mbit/s
Operating temperature (T-T)	0 - 60 °C	USB powered	✗
Storage temperature (T-T)	-40 - 70 °C	eSATA	✓
Operating relative humidity (H-H)	5 - 90%	FireWire 400	✗
Storage relative humidity (H-H)	5 - 95%	FireWire 800	✗
		Fibre Channel	✗
		Integrated USB cable	✗

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.