

Seagate STCT4000100 NAS/storage server Mini Tower Ethernet LAN Black



Brand : Seagate

Product code: STCT4000100

Product name : STCT4000100

ARM 1.2 GHz, 512 MB DDR3, NAS, 4 TB, 2BAY, LAN, USB 3.0, Seagate NAS OS 4
 Seagate STCT4000100. Total installed storage capacity: 4 TB, Supported storage drive types: HDD,
 Storage drive capacity: 2 TB. Processor family: ARM, Processor frequency: 1.2 GHz. Internal memory: 0.5
 GB, Internal memory type: DDR3. Ethernet LAN data rates: 10,100,1000 Mbit/s. Chassis type: Mini
 Tower, Product colour: Black, Cable lock slot type: Kensington

Storage		Design	
Storage drive capacity *	2 TB	Chassis type *	Mini Tower
Storage drive interface *	Serial ATA II	Product colour	Black
Storage drive size	2.5/3.5"	LED indicators	✓
RAID support *	✓	Cable lock slot	✓
RAID levels	0, 1, JBOD	Cable lock slot type	Kensington
Hot-swap drive bays	✓	Performance	
Supported file systems	ext2, ext3, ext4, FAT32, HFS+, NTFS	Type *	NAS
Storage drives installed *	✓	Device class *	Home & Home Office
Total installed storage capacity *	4 TB	Backup function *	✓
Number of storage drives installed *	2	Security algorithms	256-bit AES
Number of storage drives supported *	2	On/off switch	✓
Supported storage drive types *	HDD	Software	
Processor		Operating system installed *	Seagate NAS OS
Processor family *	ARM	Operating system version	4.0
Processor frequency *	1.2 GHz	Power	
Memory		Power supply location	External
Internal memory type	DDR3	Power supply unit (PSU) capacity	48 W
Internal memory *	0.5 GB	Power consumption (typical)	16 W
Network		Power consumption (sleep)	7 W
Ethernet LAN *	✓	Power consumption (off)	0.55 W
Ethernet LAN data rates	10,100,1000 Mbit/s	AC input voltage	100-240 V
DHCP client	✓	AC input frequency	50 - 60 Hz
DHCP server	✓	Weight & dimensions	
Jumbo frames support	✓	Width *	120 mm
Ports & interfaces		Depth *	217 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Height *	172.5 mm
Ethernet LAN (RJ-45) ports *	1	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	0 - 80%
		Storage temperature (T-T)	-40 - 65 °C
		Storage relative humidity (H-H)	0 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-JAN-2024. Prints or copies of Information are only valid on the printed Publication date