



## Seagate STCT8000100 NAS/storage server Mini Tower Ethernet LAN Black

**Brand :** Seagate

**Product code:** STCT8000100

**Product name :** STCT8000100

ARM 1.2 GHz, 512 MB DDR3, NAS, 8 TB, 2BAY, LAN 3.0, USB, Seagate NAS OS 4  
Seagate STCT8000100. Total installed storage capacity: 8 TB, Installed storage drive type: HDD,  
Supported storage drive types: HDD. Processor family: ARM, Processor frequency: 1.2 GHz. Internal  
memory: 0.5 GB, Internal memory type: DDR3. Ethernet LAN data rates: 10,100,1000 Mbit/s. Chassis  
type: Mini Tower, Product colour: Black, Cable lock slot type: Kensington



Storage		Design	
Storage drive capacity *	4 TB	Chassis type *	Mini Tower
Storage drive interface *	Serial ATA II	Product colour	Black
Storage drive size	2.5/3.5"	LED indicators	✓
RAID support *	✓	Cable lock slot	✓
RAID levels	0, 1, JBOD	Cable lock slot type	Kensington
Hot-swap drive bays	✓		
Supported file systems	ext2, ext3, ext4, FAT32, HFS+, NTFS		
Storage drives installed *	✓		
Total installed storage capacity *	8 TB		
Number of storage drives installed *	2		
Number of storage drives supported *	2		
Installed storage drive type *	HDD		
Supported storage drive types *	HDD		
Processor		Performance	
Processor family *	ARM	Type *	NAS
Processor frequency *	1.2 GHz	Device class *	Home & Home Office
		Backup function *	✓
		Security algorithms	256-bit AES
		On/off switch	✓
Memory		Software	
Internal memory type	DDR3	Operating system installed *	Seagate NAS OS
Internal memory *	0.5 GB	Operating system version	4.0
Network		Power	
Ethernet LAN *	✓	Power supply location	External
Ethernet LAN data rates	10,100,1000 Mbit/s	Power supply unit (PSU) capacity	48 W
DHCP client	✓	Power consumption (typical)	16 W
DHCP server	✓	Power consumption (sleep)	7 W
Jumbo frames support	✓	Power consumption (off)	0.55 W
		AC input voltage	100-240 V
		AC input frequency	50 - 60 Hz
Ports & interfaces		Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Width *	120 mm
Ethernet LAN (RJ-45) ports *	1	Depth *	217 mm
		Height *	172.5 mm
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	0 - 80%
		Storage temperature (T-T)	-40 - 65 °C
		Storage relative humidity (H-H)	0 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-JAN-2024. Prints or copies of Information are only valid on the printed Publication date