Seagate STDE4000100 NAS/storage server Mini Tower Ethernet LAN Black

Brand : Seagate Product code: STDE4000100

Product name: STDE4000100

Intel Dual-core 1.7 GHz, 2 GB DDR3, NAS Pro, 4 TB, 4BAY, LAN, USB 2.0, USB 3.0, Seagate NAS OS 4

Seagate STDE4000100 NAS/storage server Mini Tower Ethernet LAN Black:

Your Cloud, Your Business

The compact and sleek Seagate® NAS Pro 2-bay, 4-bay or 6-bay is the perfect asset for any business with increasing storage demands. The NAS Pro comes with Seagate NAS OS 4, providing quick, anywhere access to your private cloud and all of your centralized files, along with third-party apps and other super-practical storage features.

Seagate STDE4000100. Total installed storage capacity: 4 TB, Installed storage drive type: HDD, Supported storage drive types: HDD. Processor frequency: 1.7 GHz. Internal memory: 2 GB, Internal memory type: DDR3. Ethernet LAN data rates: 10,100,1000 Mbit/s. Chassis type: Mini Tower, Product colour: Black, Display type: LCD



Storage		Design	
Storage drive capacity * Storage drive interface * Storage drive size RAID support *	2 TB Serial ATA II 2.5/3.5" ✓	Built-in display Display type Cable lock slot Cable lock slot type	↓ LCD ↓ Kensington
RAID levels	0, 1, 5, 6, 10, JBOD	Performance	
Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed *	<pre> ✓ ext2, ext3, ext4, FAT32, HFS+, NTFS ✓ 4 TB 2</pre>	Type * Device class * Backup function * Security algorithms On/off switch	NAS Home & Home Office ✓ 256-bit AES
Number of storage drives supported	4	Software	
* Installed storage drive type * Supported storage drive types *	HDD HDD	Operating system installed * Operating system version Windows operating systems	Seagate NAS OS 4.0
Processor		supported	
Processor frequency * Processor cores	1.7 GHz 2	Linux operating systems supported Mac operating systems supported	*
Memory		Power	
Internal memory type Internal memory *	DDR3 2 GB	Power supply location Power supply unit (PSU) capacity	External 120 W
Network Ethernet LAN * Ethernet LAN data rates DHCP client	10,100,1000 Mbit/s	Power consumption (typical) Power consumption (sleep) Power consumption (off) AC input voltage AC input frequency	64 W 49 W 0.5 W 100-240 V 50 - 60 Hz
DHCP server lumbo frames support	1	Weight & dimensions	
Ports & interfaces	•	Width * Depth *	173 mm 217 mm
USB 2.0 ports quantity	1	Height *	172.5 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Operational conditions	
Ethernet LAN (RJ-45) ports *	2	Operating temperature (T-T)	0 - 40 °C
Design		Operating relative humidity (H-H) Storage temperature (T-T)	0 - 80% -40 - 65 °C
Chassis type * Product colour LED indicators	Mini Tower Black ✓	Storage relative humidity (H-H)	0 - 95%

