



## TP-Link TL-SM321B network transceiver module Fiber optic 1250 Mbit/s SFP

**Brand :** TP-Link

**Product code:** TL-SM321B-2

**Product name :** TL-SM321B



- WDM Bi-Directional SFP Module
- Supports WDM Bi-Directional technology, using a single strand of fiber, cost saving
- Pairing with TL-SM321A or MC111CS
- Compatible with T3700 series, T2700 series, T2600 series, T2500 series, T1700 series, T1600 series, T1500 series, 2/3/5 series switches and MC220L
- 1000Base-BX, WDM, Bi-Directional, SFP

**TP-Link TL-SM321B network transceiver module Fiber optic 1250 Mbit/s SFP:**



TP-LINK's TL-SM321B adopts the latest standard 1000Base-BX, transmission over a single strand of fiber, with one different wavelength going in each direction. You can extend the network distance up to 10Km(6.2 miles) with TP-LINK's Routers, Switches, Media Converters to provide high speed and stability. TP-Link TL-SM321B. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Metallic, Certification: FCC, CE. Width: 55.4 mm, Depth: 14.6 mm, Height: 12.9 mm. Number of products included: 1 pc(s), Package width: 81.5 mm, Package depth: 122.5 mm



Performance		Operational conditions	
SFP transceiver type *	Fiber optic	Operating temperature (T-T)	0 - 70 °C
Maximum data transfer rate *	1250 Mbit/s	Storage temperature (T-T)	-40 - 80 °C
Interface type *	SFP	Operating relative humidity (H-H)	10 - 90%
Single-mode fiber (SMF) supported	✓	Storage relative humidity (H-H)	5 - 90%
Multi-mode fiber (MMF) supported	✗	Weight & dimensions	
Fiber optic connector	LC	Width	55.4 mm
Fiber cable diameters supported (core/cladding)	9/125 µm	Depth	14.6 mm
SFP transceiver standard	BX	Height	12.9 mm
Maximum transfer distance	1000 m	Packaging data	
Tx wavelength (max)	1310 nm	Number of products included	1 pc(s)
Rx wavelength (max)	1550 nm	User guide	✓
Networking standards	IEEE 802.3z	Package width	81.5 mm
Wavelength-division multiplexing (WDM)	✓	Package depth	122.5 mm
		Package height	38.5 mm
		Package weight	60 g
Features		Technical details	
Product colour	Metallic	Sustainability certificates	RoHS
Certification	FCC, CE	Logistics data	
		Harmonized System (HS) code	85369010



6935364072940



6935364010614



0845973030964



845973030964

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.