QNAP TS-1232XU-RP NAS Rack (2U) Ethernet LAN Aluminium, Black Alpine AL-324

Brand : QNAP

Product code: TS-1232XU-RP-4G-US

Product name : TS-1232XU-RP

- The built-in 10GbE SFP+ ports deliver high speed for mission-critical applications such as database hosting and VM storage

- One PCIe 2.0 $\times 2$ slot (×4 length) is available for adding a 10GbE port and/or M.2 SSD slots. With SSDs installed, Qtier auto tiering can be enabled to optimize storage utilization

- Snapshots add an extra layer of protection to your disaster recovery plan, giving you the flexibility to create and revert snapshots locally and/or remotely

- The Hybrid Backup Sync app completes your backup strategies, allowing you to back up, restore and sync files locally and remotely

- QNAP's Virtual JBOD technology can be used to expand remote NAS capacity, ensuring all available space can be fully utilized

- The hot-swappable redundant power supply ensures high reliability and maximum system uptime Alpine AL-324 (1.7GHz), 4GB DDR4 (2400MHz), 10GbE





BitTorrent

Storage		Performance	
Supported storage drive interfaces RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Supported file systems Storage drives installed * Auto-rebuild Bad block scan Disk roaming Processor	<pre></pre>	Number of users Noise level Third-party support Video input channels Snapshot Management protocols Web-based management Share folder access right management Security algorithms Access Control List (ACL) Reset button	4096 user(s) 31.7 dB ✓ 8 channels ✓ SNMP ✓ 256-bit AES, FIPS 140-2, HTTPS, SNMP, SSH ✓
Processor family *	Annapurna Labs	On/off switch	✓
Processor model *	Alpine AL-324	Built-in BitTorrent client	<
Processor cores	4	Built-in iTunes server	4
Memory		Built-in FTP server	✓ Apple Safari 7+, Google Chrome,
Internal memory type Memory clock speed Maximum RAM supported Memory slots Flash memory	DDR4 2400 MHz 16 GB 1x DIMM 512 MB	Browser supported System log Hot spare S.M.A.R.T. support	Microsoft Internet Explorer 10+, Mozilla Firefox ✓ ✓
Network		Share folder	512
Ethernet LAN *	4	Software	
Ethernet LAN data rates Ethernet LAN data rate supported (max)	10,100,1000,10000 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version	QNAP Turbo System 4.3.4
Wi-Fi DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Link aggregation Dynamic DNS (DDNS)	× √ √ √ √ √		
WLAN adapter supported	✓		

Ports & interfaces		Software	
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports *	 ✓ 4 2 SFP+ 2 		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7
Design			Enterprise, Windows 7 Enterprise
Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators	Rack (2U) Active Aluminium, Black 2 fan(s) 7 cm HDD, LAN, Status	Windows 7 Professional, Wind Professional x64, Windows 7 Starter, Windows 7 Starter x64 Windows 7 Ultimate, Windows	Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7
Performance			Windows 8, Windows 8 Enterprise,
Type * Device class *	NAS Small & Medium Business		Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64
Backup function *	4	Linux operating systems supported	✓
Backup features Buzzer	Cloud, iSCSI LUN ✓	Mac operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
		Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
		Power	
		Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage	Built-in 250 W 2 ✓ 77.09 W 42.61 W 100 - 240 V
		Output voltage	12 V
		Weight & dimensions	
		Width *	482 mm

Depth *

Height *

Weight

Package weight

Packaging content Cables included

Quick installation guide

Operational conditions Operating temperature (T-T)

Operating relative humidity (H-H)

534 mm

89 mm

11.3 kg

17.3 kg

0 - 40 °C

5 - 95%

1

AC, LAN (RJ-45)

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.