

Seagate Enterprise Nytro 3332 2.5" 960 GB SAS 3D eTLC

Brand : Seagate **Product family:** Enterprise **Product code:** XS960SE70084

Product name : Nytro 3332

- 12 Gb/s SAS interface and dual ports for 24x7 performance
 - Low latency and high QoS for better responsiveness and user experience
 - Easily manage and monitor SSD health with SeaChest
 - Three endurance options to meet workload, deployment and TCO demands
 - Ensures reliable data protection for mission-critical applications
 - Seagate Secure™ with Secure Download and Diagnostics (SD&D), SED, and SED
 - FIPS 140-2 options for advanced data security
 - Built for easy integration with Linux and Microsoft OS
- 960 GB, 2.5", 12 Gb/s SAS, 3D eTLC, 2150 / 1300 MB/s, Standard encryption

Seagate Enterprise Nytro 3332 2.5" 960 GB SAS 3D eTLC:

High capacity SSD with drive monitoring, government-grade encryption, and scalable, secure performance for demanding enterprise workloads.

Seagate Enterprise Nytro 3332. SSD capacity: 960 GB, SSD form factor: 2.5", Read speed: 2150 MB/s, Write speed: 1300 MB/s, Data transfer rate: 12 Gbit/s, Component for: Server/workstation



Features		Power	
SSD form factor *	2.5"	Power consumption (idle)	4.6 W
SSD capacity *	960 GB	Operational conditions	
Interface *	SAS	Operating temperature (T-T)	0 - 70 °C
Memory type *	3D eTLC	Storage temperature (T-T)	-40 - 75 °C
NVMe *	✗	Operating relative humidity (H-H)	5 - 95%
Component for *	Server/workstation	Storage relative humidity (H-H)	5 - 95%
Hardware encryption *	✓	Operating shock	1000 G
Data transfer rate	12 Gbit/s	Non-operating shock	1000 G
Read speed	2150 MB/s	Maximum non-operating altitude	12192 m
Write speed	1300 MB/s	Maximum operating altitude	3048 m
Random read (4KB)	170000 IOPS	Weight & dimensions	
Random write (4KB)	70000 IOPS	Width	70.1 mm
S.M.A.R.T. support	✓	Depth	100.5 mm
ECC	✓	Height	15 mm
JEDEC standard	✓	Weight	165 g
Mean time between failures (MTBF)	2500000 h	Logistics data	
Power		Harmonized System (HS) code	84717070
Operating voltage	12 V		
Current	0.21 A		



0763649144015



763649144015



8719706024716



8592978367237

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.