



## Seagate BarraCuda 120 2.5" 2 TB Serial ATA 3D TLC

**Brand :** Seagate

**Product family:** BarraCuda

**Product code:**  
ZA2000CM1A003

**Product name :** 120

2TB, 2.5 inch, SATA 6 Gb/s, 3D TLC, NAND

[Seagate BarraCuda 120 2.5" 2 TB Serial ATA 3D TLC:](#)

Speed Up Your Computer

Take your data to the next level of performance, reliability, and efficiency with one of our Seagate® BarraCuda™ solid-state drives.

BarraCuda SSD solutions come in both 2.5 SATA form factors, perfect for ultra thin and ultra small laptops, mini PCs, and desktop PCs that need next-level SSD speed for accelerated applications and multitasking.



### Get an SSD Boost in Performance

BarraCuda SSD

Advanced Speed

Unlock maximum SATA 6 Gb/s SSD speeds with 3D TLC NAND that delivers the speed you need.

BarraCuda SSD

Coveted Versatility

Easily upgrade from hard drives with a plug-and-play 2.5-inch 7 mm form factor and SATA interface

Seagate BarraCuda 120. SSD capacity: 2 TB, SSD form factor: 2.5", Read speed: 560 MB/s, Write speed:

540 MB/s, Data transfer rate: 6 Gbit/s, Component for: PC

Features		Operational conditions	
SSD form factor *	2.5"	Storage temperature (T-T)	-40 - 85 °C
SSD capacity *	2 TB	Non-operating shock	1500 G
Interface *	Serial ATA	Technical details	
Memory type *	3D TLC	Sustainability certificates	RoHS
NVMe *	✗	Weight & dimensions	
Component for *	PC	Width	70.1 mm
Hardware encryption *	✗	Depth	100.3 mm
Data transfer rate	6 Gbit/s	Height	7.1 mm
Read speed	560 MB/s	Weight	50 g
Write speed	540 MB/s	Packaging data	
Random read (4KB)	90000 IOPS	Package width	109 mm
Random write (4KB)	90000 IOPS	Package depth	24 mm
S.M.A.R.T. support	✓	Package height	155 mm
TRIM support	✓	Package weight	100 g
Mean time between failures (MTBF)	1800000 h	Package type	Box
Windows operating systems supported	Windows 10, Windows 7, Windows 8.1	Logistics data	
Linux operating systems supported	✓	Master (outer) case width	292 mm
Power		Master (outer) case length	153 mm
Power consumption (average)	2.8 W	Harmonized System (HS) code	84717070
Operational conditions		Master (outer) case height	140 mm
Operating temperature (T-T)	0 - 70 °C	Master (outer) case net weight	1.2 g
		Products per master (outer) case	10 pc(s)



0763649139318



763649139318

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.