



Seagate BarraCuda 510 M.2 1 TB PCI Express 3.0 3D TLC NVMe

Brand : Seagate

Product family: BarraCuda

Product code:
ZP1000CM3A001

Product name : 510

1TB, 3D TLC, PCIe 3.0 x4, NVMe 1.3, M.2 2280-S2

[Seagate BarraCuda 510 M.2 1 TB PCI Express 3.0 3D TLC NVMe:](#)

Speed Up Your Computer.

Take your data to the next level of performance, reliability, and efficiency with one of our Seagate® BarraCuda® solid state drives.

BarraCuda solid state drives come in both M.2 2280 form factors, perfect for ultra thin and ultra small laptops, mini PCs, and desktop PCs that need next-level SSD speed for accelerated applications and multitasking.



M.2. NVMe PCIe Gets You There Faster.

Ultrafast Speed

Unleash the performance of PCIe NVMe speeds that are 6x faster than SATA SSD.

Dynamic Versatility

Upgrade ultra-thin laptops as well as mini and desktop PCs with an M.2 SSD.

Solid Reliability

Leverage BarraCuda durability with a 5 year warranty, 1.8M hours MTBF and up to 320 total terabytes written.

Seagate BarraCuda 510. SSD capacity: 1 TB, SSD form factor: M.2, Read speed: 3400 MB/s, Write speed: 3000 MB/s, Component for: PC

Features		Operational conditions	
NVMe version	1.3	Storage temperature (T-T)	-40 - 85 °C
SSD form factor *	M.2	Technical details	
SSD capacity *	1 TB	Sustainability certificates	RoHS
Interface *	PCI Express 3.0	Weight & dimensions	
Memory type *	3D TLC	Width	22.1 mm
NVMe *	✓	Depth	80.2 mm
Component for *	PC	Height	2.23 mm
Hardware encryption *	✗	Weight	8.7 g
Read speed	3400 MB/s	Packaging data	
Write speed	3000 MB/s	Package width	109 mm
Random read (4KB)	600000 IOPS	Package depth	134.2 mm
Random write (4KB)	600000 IOPS	Package height	24 mm
M.2 SSD size	2280 (22 x 80 mm)	Package weight	61 g
S.M.A.R.T. support	✓	Logistics data	
TRIM support	✓	Master (outer) case width	278 mm
Mean time between failures (MTBF)	1800000 h	Master (outer) case length	129 mm
Power		Master (outer) case height	169 mm
Power consumption (average)	5.3 W	Master (outer) case net weight	910 g
Operational conditions		Products per master (outer) case	10 pc(s)
Operating temperature (T-T)	0 - 70 °C		



0763649138236



763649138236



8719706019941

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.