



## Belkin F9K1112 wireless router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Black

**Brand :** Belkin

**Product code:** F9K1112

**Product name :** F9K1112

AC 1000 DB Wi-Fi Dual-Band AC+ Gigabit Router, Mac, Windows, IPSec L2TP, Ethernet, DHCP, 2.4/5 GHz, SSID, WEP, WPA, WPA2, RJ45, HTTP, 32 WLAN, 4 LAN, Ethernet 10Base-T/100Base-TX/1000Base T (4), Black

Belkin F9K1112. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 650 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Cabling technology: 10/100/1000Base-T(X). Security algorithms: WEP, WPA, Authentication method: SSID. Switching protocols: Ethernet, Routing protocols: IP. Product colour: Black



<b>WAN connection</b>		<b>Protocols</b>	
Ethernet WAN *	✓	Universal Plug and Play (UPnP)	✗
<b>Wireless LAN features</b>		Switching protocols	Ethernet
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Routing protocols	IP
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	<b>Design</b>	
WLAN data transfer rate (max) *	650 Mbit/s	Product colour	Black
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	<b>Packaging content</b>	
Number of WLAN connections (max)	32	AC adapter included	✓
<b>Network</b>		<b>Antenna</b>	
Ethernet LAN *	✓	Antenna design *	Internal
Ethernet LAN interface type *	Gigabit Ethernet	<b>Features</b>	
Ethernet LAN data rates	10,100,1000 Mbit/s	Plug and Play	✗
Cabling technology	10/100/1000Base-T(X)	<b>Power</b>	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Output voltage	12 V
<b>DSL features</b>		<b>Operational conditions</b>	
Internal modem	✗	Operating temperature (T-T)	0 - 40 °C
<b>Ports &amp; interfaces</b>		Storage temperature (T-T)	-20 - 65 °C
Ethernet LAN (RJ-45) ports *	4	Operating relative humidity (H-H)	10 - 85%
<b>Management features</b>		<b>System requirements</b>	
Web-based management	✓	Windows operating systems supported	✓
Reset button	✓	Mac operating systems supported	✓
<b>Security</b>		<b>Other features</b>	
Security algorithms	WEP, WPA	WLAN data transfer rates supported	650 Mbit/s
Authentication method	SSID	Bandwidth (first)	2.4 GHz
Firewall	✓	Bandwidth (second)	5 GHz
Stateful Packet Inspection (SPI)	✓	USB ports quantity	2
Network address translation (NAT)	✓	Supported protocols	IPSec ,L2TP
		Input current	0.8 A

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-JAN-2024. Prints or copies of Information are only valid on the printed Publication date